



Main

| | |
|--------------------------------|--|
| Range of product | NSX100...250 |
| Product or component type | Control unit |
| Range compatibility | Compact NSX100 Compact NSX160 Compact NSX250 |
| Device application | Generator |
| Poles description | 3P |
| Protected poles description | 3t |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Trip unit name | Micrologic 2.2 G |
| Trip unit technology | Electronic |
| Trip unit protection functions | LSol |
| Protection type | L : for overload protection (long time) So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection |
| Trip unit rating | 40 A at 40 °C |

Complementary

| | |
|---|---|
| Mounting mode | Fixed |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| Long time pick-up adjustment type Ir | Adjustable 9 settings |
| [Ir] long time pick-up adjustment range | 0.9...1 x Io |
| Long time delay adjustment type | Fixed |
| [Tr] long-time delay adjustment range | 15 s at 1.5 x Ir 0.35 s at 7.2 x Ir 0.5 s at 6 x Ir |
| Thermal memory | 20 minutes before and after tripping |

| | |
|---|--------------|
| Short-time pick-up adjustment type Isd | Adjustable |
| [Isd] short-time pick-up adjustment range | 1.5...9 x Ir |
| Short-time delay adjustment type | Fixed |
| [Tsd] short-time delay adjustment range | 0.14 s |
| Instantaneous pick-up adjustment type li | Fixed |
| [li] instantaneous pick-up adjustment range | 600 A |

Environment

| | |
|---------------------------------------|--------------------------|
| Standards | EN/IEC 60947-2 UL 508 |
| Product certifications | CCC Marine EAC |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -50...85 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|