



## Main

Range compatibility	PacDrive 3
Product or component type	Servo motor
Device short name	SH3.....P

## Complementary

Maximum mechanical speed	3800 rpm
[Us] rated supply voltage	115...480 V
Network number of phases	Three phase
Continuous stall current	33.2 A
Continuous stall torque	94.4 N.m at 115...480 V three phase
Peak stall torque	330 N.m at 115...480 V three phase
Nominal output power	4450 W at 115 V three phase 7790 W at 230 V three phase 10620 W at 400 V three phase 10100 W at 480 V three phase
Nominal torque	84.9 N.m at 115 V three phase 74.4 N.m at 230 V three phase 50.7 N.m at 400 V three phase 40.2 N.m at 480 V three phase
Nominal speed	500 rpm at 115 V three phase 1000 rpm at 230 V three phase 2000 rpm at 400 V three phase 2400 rpm at 480 V three phase
Maximum current Irms	136.1 A
Shaft end	Smooth shaft
Shaft diameter	38 mm
Shaft length	80 mm
Key width	10 mm
IP degree of protection	IP54 shaft bushing without shaft seal ring: conforming to EN/IEC 60034-5

IP65 motor: conforming to EN/IEC 60034-5  
 IP65 shaft bushing: conforming to EN/IEC 60034-5

Encoder type	Absolute single turn SinCos Hiperface
Speed feedback resolution	128 periods
Holding brake	Without
Mounting support	International standard flange
Motor flange size	205 mm
Torque constant	2.76 N.m/A at 120 °C
Back emf constant	172 V/krpm at 20 °C
Number of motor poles	5
Rotor inertia	190 kg.cm <sup>2</sup>
Stator resistance	0.2 Ohm
Stator inductance	6.3 mH
Maximum radial force Fr	4500 N at 1000 rpm 3570 N at 2000 rpm 3120 N at 3000 rpm
Maximum axial force Fa	740 N
Type of cooling	Natural convection
Length	489 mm
Centring collar diameter	180 mm
Centring collar depth	4 mm
Number of mounting holes	4
Mounting holes diameter	14 mm
Circle diameter of the mounting holes	215 mm
Product weight	67 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------