



Main

Range of product	Harmony Hub
Product or component type	Communication module
Device short name	ZBRCETH
Communication port protocol	Modbus TCP

Complementary

Integrated connection type	Ethernet RJ45 - 2 twisted pairs - class D
Transmission rate	10/100 Mbit/s
Communication service	Static IP DHCP, Modbus TCP/IP BOOTP
Physical interface	RJ45 - 10BASE-T RJ45 - 100BASE-TX
Marking	CE
Local signalling	1 LEDtransmission activity: 1 LEDreception activity (RX): 1 LEDmodule status: 1 LEDnetwork status:
Product destination	ZBRN1 wireless Harmony Hub
Product weight	0.044 kg

Environment

Product certifications	CSA UL 508 BTL UL 873 UL 60730-1
Electromagnetic compatibility	EMC immunity conforming to EN/IEC 61000-6-1 EMC immunity level 2 conforming to EN/IEC 60730-1 Electrostatic discharge level 3B conforming to IEC 61000-4-2 Radiated RF fields level 3A conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test level 4B conforming to IEC 61000-4-4 Surge immunity test level 3 conforming to IEC 61000-4-5 Conducted RF disturbances level 3A conforming to IEC 61000-4-6 Conducted EMC level 2 conforming to EN/IEC 60730-1 Conducted EMC conforming to EN/IEC 61000-6-3 EMC immunity conforming to IEC 61800-3

Conducted EMC conforming to IEC 61800-3 category C1

IP degree of protection	IP20
Ambient air temperature for operation	-20...65 °C
Ambient air temperature for storage	-25...70 °C
Relative humidity	5...95 % without condensation
Pollution degree	2
Operating altitude	0...2000 m
Storage altitude	0...3048 m
Vibration resistance	1.5 mm (f = 3...13 Hz) 1 mm (f = 13...23 Hz) 2 gn (f = 23...150 Hz)
Shock resistance	15 gn for 11 ms

Contractual warranty

Warranty	18 months
----------	-----------