

XVMC34

illuminated unit - Ø 45 - red - BA 15d - bulb not included - ≤ 230 V AC DC



Main

Range of product	Harmony XVM
Product or component type	Indicator bank
Beacon or indicator bank unit type	Illuminated unit
Component name	XVM
Light source	Bulb not included, red
Bulb type	Incandescent with BA 15d base Super bright LED Flash discharge tube
[Us] rated supply voltage	≤ 230 V AC/DC

Complementary

Mounting diameter	45 mm
Assembly style	Customer assembly
Maximum power dissipation in W	5 W
Connections - terminals	Screw terminals, 1 x 0.325...1 x 1.5 mm ²
Marking	CE
[Ui] rated insulation voltage	250 V conforming to IEC 60947-1
Nominal voltage limit	0.85...1.1 Un conforming to IEC 60947-5-1
[Uimp] rated impulse withstand voltage	IEC 60947-1 4 kV
Luminance	650 cd/m ²
CAD overall width	47 mm
CAD overall height	65 mm
CAD overall depth	47 mm
Product weight	0.04 kg

Environment

Product certifications	CCC
Standards	EN/IEC 60947-1

EN/IEC 60947-5-1

Ambient air temperature for storage	-25...70 °C
Ambient air temperature for operation	-10...50 °C
IP degree of protection	IP40 any position except vertical position conforming to IEC 60529 IP42 vertical position conforming to IEC 60529
Electrical shock protection class	Class I aluminium tube mounting conforming to IEC 60947-1 Class I aluminium tube mounting conforming to IEC 60947-5-1 Class I aluminium tube mounting conforming to IEC 61140 Class II base mounting conforming to IEC 60947-1 Class II base mounting conforming to IEC 60947-5-1 Class II base mounting conforming to IEC 61140
Protective treatment	TC

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins


Contractual warranty

Warranty	18 months
----------	-----------

Customer Assembled Tower Light

Dimensions

Below drawing shows a tower light with 3 illuminated stages. Select the number of stages according to the product characteristics in order to get b dimension.



- (1) Cover (included with base unit XVMC21/C29•)
- (2) Illuminated unit
- (3) Base unit XVMC21 (without buzzer) or XVMC29• (with buzzer), to be ordered separately
- (4) Fixing base XVMZ0•/Z0•T, to be ordered separately

Number of illuminated units (ref. 2)	b in mm	b in in.
1	127	5.00
2	192	7.56
3	257	10.12
4	322	12.68
5	387	15.24