



Main

Range	Linergy
Product name	Linergy DX
IP degree of protection	IPxx B
Product or component type	Distribution block
Accessory / separate part category	Current distribution accessory
Product compatibility	Spacial enclosures

Complementary

Mounting support	DIN rail
Installed device	Acti 9: fixed C120 with earth leakage protection - control: toggle Acti 9: fixed C120 without earth leakage protection - control: toggle Acti 9: fixed iC120 with earth leakage protection - control: toggle Acti 9: fixed iC120 without earth leakage protection - control: toggle Compact: fixed INS40 - control: direct front rotary handle - vertical installation Compact: fixed INS63 - control: direct front rotary handle - vertical installation Compact: fixed INS100 - control: direct front rotary handle - vertical installation Compact: fixed INS125 - control: direct front rotary handle - vertical installation Compact: fixed INS160 - control: direct front rotary handle - vertical installation Fupact: fixed ISFT160 - control: fuse carriers handle - vertical installation Fupact: fixed ISFT100N - control: fuse carriers handle - vertical installation Multi 9: fixed NG125 with earth leakage protection - control: toggle Multi 9: fixed NG125 without earth leakage protection - control: toggle Multi 9: fixed NG125 NA - control: toggle Compact: fixed NG160 with earth leakage protection - control: toggle Compact: fixed NG160 without earth leakage protection - control: toggle Compact: fixed NG160 NA without earth leakage protection - control: toggle Fupact: fixed INF100...160 - control: extended rotary handle - vertical installation Compact: fixed NSXm without earth leakage protection - control: toggle - vertical installation Compact: fixed NSXm without earth leakage protection - control: toggle - horizontal installation Compact: fixed NSXm without earth leakage protection - control: direct rotary handle - horizontal installation Compact: fixed NSXm with earth leakage protection - control: toggle - vertical installation Compact: fixed NSXm with earth leakage protection - control: toggle - horizontal installation
Poles description	1P

[Ue] rated operational voltage	690 V AC
[Ui] rated insulation voltage	750 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	160 A
[Icw] rated short-time withstand current	5.5 kA for 1 s
[Ipk] rated peak withstand current	24 kA
I ² t on activation	30250000 A ² .s
Connections - terminals	Supply: tunnel type terminal 70 mm ² (flexible) Supply: tunnel type terminal 70 mm ² (rigid) Distribution: spring terminal, 6 x 6...16 mm ² (flexible) Distribution: spring terminal, 6 x 6...16 mm ² (rigid)
Total number of 18 mm modules	2
Height	95 mm
Width	36 mm
Depth	70 mm
Product weight	0.1 kg
Colour	Anthracite grey (RAL 7016)

Environment

Pollution degree	3
Resistance to incandescent wire	960 °C conforming to IEC 60695-2-11
Standards	IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma IEC 60947-7-1
Product certifications	ASEFA

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------