



Main

Range	Linergy
Product name	Linergy DX
Product or component type	Flexible connection
Accessory / separate part category	Current distribution accessory
Product compatibility	NG125

Complementary

Cubicle-device connection	Linergy DX distribution block
Installation description	<p>Floor-standing duct - width 300 mm</p> <p>Wall-mounted duct - width 300 mm</p> <p>Cubicle - width 650 mm</p> <p>Floor-standing enclosure - width 600 mm</p> <p>Wall-mounted enclosure - width 600 mm</p> <p>Cubicle - width 800 mm</p> <p>Pack enclosure - width 555 mm</p> <p>Pack enclosure - width 600 mm</p>
Installed device	<p>Multi 9: fixed NG125 without earth leakage protection - control: toggle</p> <p>Multi 9: fixed NG125 with earth leakage protection - control: toggle</p> <p>Compact: fixed INS40 - control: direct front rotary handle vertical installation</p> <p>Compact: fixed INS63 - control: direct front rotary handle vertical installation</p> <p>Compact: fixed INS100 - control: direct front rotary handle vertical installation</p> <p>Compact: fixed INS125 - control: direct front rotary handle vertical installation</p> <p>Compact: fixed INS160 - control: direct front rotary handle vertical installation</p> <p>Acti 9: fixed iC120 with earth leakage protection - control: toggle</p> <p>Acti 9: fixed iC120 without earth leakage protection - control: toggle</p> <p>Multi 9: fixed NG125 NA - control: toggle</p> <p>Compact: fixed NG160 NA without earth leakage protection - control: toggle</p> <p>Acti 9: fixed C120 with earth leakage protection - control: toggle</p> <p>Acti 9: fixed C120 without earth leakage protection - control: toggle</p> <p>Compact: fixed NG160 with earth leakage protection - control: toggle</p> <p>Compact: fixed NG160 without earth leakage protection - control: toggle</p> <p>Compact: fixed NSXm without earth leakage protection - control: toggle vertical installation</p> <p>Compact: fixed NSXm with earth leakage protection - control: toggle vertical installation</p>
Condition of use	Additional connector needed for INS40...160 (to be ordered separately)

[Ie] rated operational current	125 A
Quantity per set	Set of 4
Length	240 mm
Product weight	0.52 kg

Environment

Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------