



Price\* : 51.01 GBP



## Main

Range	TeSys
Product name	TeSys LS1
Product or component type	Fuse-disconnector
Device short name	LS1D
Poles description	3P

## Complementary

Mounting support	Rail
Mounting position	Vertical (tolerance: +/- 23°)
Control type	Toggle
[Ue] rated operational voltage	600 V
[Ie] rated operational current	30 A for power circuit
Local signalling	Blown fuse indication
Fuse size	0.41 x 1.50 in
Fuse type	CC
Connections - terminals	Screw clamp terminals 2 cable(s) 1...6 mm <sup>2</sup> solid Screw clamp terminals 2 cable(s) 1...6 mm <sup>2</sup> flexible without cable end Screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> flexible with cable end
Tightening torque	1.7 N.m on screw clamp terminals

## Environment

Standards	IEC 60947-1 IEC 60947-2 IEC 60947-4-1 UL 508
Product certifications	UL CSA
IP degree of protection	IP20

Protective treatment	TH
Ambient air temperature for operation	-50...70 °C operation
Height	89 mm
Width	45 mm
Depth	68.3 mm
Product weight	0.3 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------