



Price\* : 244.73 GBP



## Main

Range of product	Harmony XVS
Product or component type	Multisound siren
Device short name	XVS

## Complementary

Colour	White
Material	PC (polycarbonate): back cover PC (polycarbonate)/ABS (acrylonitrile butadiene-styrene): front PC (polycarbonate)/ABS (acrylonitrile butadiene-styrene): back
Product weight	1.2 kg
Marking	CE
Mounting support	Bracket
Fixing mode	3 holes Ø 9 mm
[Uimp] rated impulse withstand voltage	4 kV
Current consumption	50 mA at 240 V
Electrical connection	Cable: 6.5...8.5 mm, 0.33 mm <sup>2</sup> / AWG AWG 22 (signalling circuit) Cable: 6.5...8.5 mm, 0.52 mm <sup>2</sup> / AWG AWG 20 (power circuit)
Width	140 mm
Height	114 mm
Depth	223 mm

## Environment

Signalling type	43 tones siren
Standards	EN 61000-6-3 EN 60947-5-1 EN 60947-01 EN 61000-6-2
Product certifications	UL

Protective treatment	TC
Ambient air temperature for storage	-35...70 °C
Ambient air temperature for operation	-10...50 °C
Overvoltage category	Class II conforming to EN/IEC 61140
IP degree of protection	IP53 conforming to EN/IEC 60529
[Us] rated supply voltage	240 V AC
Noise level	0...105 dB (continuous or intermittent tone) at 1 m

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>

### Contractual warranty

Warranty	18 months
----------	-----------

## Siren

### Dimensions

mm  
in.

