



## Main

|                                    |                      |
|------------------------------------|----------------------|
| Range                              | Acti 9               |
| Product or component type          | Comb busbar          |
| Accessory / separate part category | Connection accessory |
| Lines description                  | 1L + N               |
| Length in 18 mm modules            | 57                   |

## Complementary

|                                |  |
|--------------------------------|--|
| Number of ways                 | 28 ways N + 1 L  |
| Poles configuration for 1 way  | 1 x 1P + N<br>1 x 2P   |
| Connection pitch               | 18 mm  |
| Connector type                 | Tooth  |
| Distance between way           | 36 mm  |
| Marking                        | N L  |
| Insulation                     | Insulated  |
| Device presentation            | Cuttable   |
| Provided equipment             | Set of 10 end piece  |
| [Ie] rated operational current | 100 A at 40 °C   |
| [Ue] rated operational voltage | 415 V AC   |
| [Ui] rated insulation voltage  | 500 V AC conforming to IEC 61439-2   |
| Mounting mode                  | Horizontal   |
| Mounting location              | Top or bottom on tunnel type terminals<br>Top or bottom on double terminal |
| 9 mm pitches                   | 114  |
| Width                          | 1000 mm  |
| Colour                         | White (RAL 9003)   |
| Range compatibility            | Acti 9 iC60<br>Acti 9 iK60<br>Acti 9 iID                                   |

Acti 9 iID K  
Acti 9 iSW  
Acti 9 iSW-NA  
Multi 9 C60

## Environment

|                         |   |
|-------------------------|---|
| Standards               | IEC 60947-7-1<br>IEC 61439-2                |
| Fire resistance         | 960 °C ( 30 s ) conforming to IEC 60695-2-1 |
| Pollution degree        | 3 conforming to IEC 60947-7-1               |
| IP degree of protection | IP20 with end-pieces and tooth covers       |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope)                 |
| Circularity Profile        | No need of specific recycling operations  |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|