Dimensions



Model Number

V3S-GM-BK10M-PUR-U

Cable connector, M8, 3-pin, PUR cable

Features

- UL Recognized Component
- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Gold plated contacts
- Flame resistant cable
- Resistant to microbes and hydrolysis
- Halogen-free
- Suitable for drag chains

Technical data

General specifications		
Number of pins		3
Connection 1		Male connector
Construction type 1		straight
Threading 1		M8
Connection 2		cable end
UL File Number		E231213
Electrical specifications		
Operating voltage	U_B	max. 48 V AC / 60 V DC
Operating current	I_B	max. 3 A
Contact resistance		< 10 mΩ
Ambient conditions		
Ambient temperature		40 ... 90 °C (104 ... 194 °F) cable, fixed: -40 ... 80 °C (-40 ... 176 °F) cable, flexing: -20 ... 80 °C (-4 ... 176 °F)
Pollution degree		3
Mechanical specifications		
Pin diameter		1 mm
Degree of protection		IP67
Cable code		Li 9Y 11Y 3 x 0.34
Material		
Contacts		CuSn / Au
Contact surface		Au
Body		TPU, black
Cable		PUR
Sleeve connector		Diecast zinc
Core insulation		PP
Cable		extra-fine wire, flexible
Sheath diameter		Ø 4.3 mm
Bending radius		> 10 x cable diameter, moving > 5 x cable diameter, fixed
Color		black
Cores		3 x 0.34 mm^2
Conductor construction		42 x 0.1 mm Ø
Length	L	10 m
Drag chain suitability		
Drag chain cycles		≥ 5000000
Motion velocity		≤ 3.3 m/s
Acceleration		≤ 5 m/s^2
Torsional stress		± 180 °/m
Flammability		
Contact carrier		94 HB
Housing		94 V-2
Cable		FT2

Electrical connection



Release date: 2019-07-15 13:51 Date of issue: 2019-07-15 240807-0002_eng.xml

Compliance with standards and directives	
Standard conformity	
Degree of protection	EN 60529:2000
Flammability	Body: UL 94 Line: UL 1581 Section 1061; IEC 60332-1-2:2004
Specification	connector M8 x 1 : IEC 61076-2-104
Approvals and certificates	
UL approval	cURus AWM 20549 AWM I/II A/B 80°C 300V FT2 (cable)

Release date: 2019-07-15 13:51 Date of issue: 2019-07-15 240807-0002_eng.xml

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".
Pepperl+Fuchs Group www.pepperl-fuchs.com
USA: +1 330 486 0001 fa-info@us.pepperl-fuchs.com
Germany: +49 621 776 1111 fa-info@de.pepperl-fuchs.com
Singapore: +65 6779 9091 fa-info@sg.pepperl-fuchs.com
PEPPERL+FUCHS