



Model Number

V1-W-N-20M-PUR

Female Cordset, M12, NAMUR

Features

- Suitable for NAMUR technology
- Blue sheath
- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Gold plated contacts
- Degree of protection IP67 / IP68 / IP69K
- Suitable for routing intrinsically safe circuits in accordance with DIN EN 60079-14:2014

Technical data

General specifications

Number of pins	2
----------------	---

Electrical specifications

Operating voltage	U_B	max. 250 V AC/DC
Test voltage		> 500 V _{eff} AC
Operating current	I_B	max. 4 A
Contact resistance		< 10 mΩ
Inductance		0.55 mH / km
Capacitance		88.3 nF / km

Ambient conditions

Ambient temperature	Body: -40 ... 90 °C (-40 ... 194 °F) cable -25 ... 100 °C (-13 ... 212 °F)
---------------------	---

Pollution degree	3
------------------	---

Mechanical specifications

Contact elements	spring-loaded contact socket
------------------	------------------------------

Pin diameter	1 mm
--------------	------

Degree of protection	IP67 / IP68 / IP69K
----------------------	---------------------

Material

Contacts	CuSn / Au
----------	-----------

Contact surface	Au
-----------------	----

Body	TPU, black
------	------------

Cable	PUR
-------	-----

Slotted nut	Diecast zinc
-------------	--------------

Core insulation	PVC
-----------------	-----

Cable	extra-fine wire, flexible
-------	---------------------------

Sheath diameter	Ø 4.8 mm
-----------------	----------

Bending radius	> 15 x cable diameter, moving > 10 x cable diameter, fixed
----------------	---

Color	blue
-------	------

Cores	2 x 0.34 mm ²
-------	--------------------------

Conductor construction	42 x 0.1 mm Ø
------------------------	---------------

Length	L 20 m
--------	--------

Flammability

Contact carrier	94 HB
-----------------	-------

Housing	94 V-2
---------	--------


Compliance with standards and directives

Standard conformity	
---------------------	--

Degree of protection	EN 60529
----------------------	----------

Standards	IEC 61076-2-101
-----------	-----------------

Electrical connection



Electrical connection

1	BN
2	BU