

MAIN SWITCH 4-POLE FLOOR MOUNTING IU=160A P/AC-23A AT 400V=75KW WITH DOOR COUPLING ROTARY MECHANISM RED/YELLOW (EMERG. STOP) FRONT/FOUR-HOLE MOUNTING



Similar to image

General technical details:

product brand name		SENTRON
product designation		main and EMERGENCY-OFF switches
Type from device		fixed mounting
Design of the operating mechanism		knob-operated mechanism, red/yellow
Protection class IP		IP65
Number of poles		4
Acceptability for application		
<ul style="list-style-type: none"> • switch disconnecter • main switch • safety cut-out switch • emergency stop switch • maintenance/repair switch 		<p>Yes</p> <p>Yes</p> <p>No</p> <p>No</p> <p>Yes</p>
Product equipment / interlock		Yes
Type of the driving mechanism / motor drive		No
Product extension / optional		
<ul style="list-style-type: none"> • motor drive • voltage trigger 		<p>No</p> <p>No</p>
Ambient temperature / during operating	°C	-25 ... +55

Insulation voltage / rated value	V	690
Impulse voltage resistance / rated value	V	8,000
Active power loss / per conductor / typical	W	36
Mechanical operating cycles as operating time / of the main contacts / typical		100,000
Protection against electrical shock		finger-safe
Item designation / according to DIN EN 61346-2		S
Item designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		S

Main circuit:

Continuous current / rated value	A	160
Operating current / at AC-21 / rated value	A	160
Short-time current resistance (I _{cw}) / at 690 V / limited to 1 s / rated value	A	4,000
Operating frequency	Hz	50 ... 60
Operating voltage / at 50/60 Hz / for AC / rated value	V	690
Service power / at AC-3		
• at 400 V / rated value	kW	50
• at 690 V / rated value	kW	37
Service power / at AC-23 A		
• at 400 V / rated value	kW	75
• at 690 V / rated value	kW	45
Operating cycles / maximum	1/h	50

Auxiliary circuit:

Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		0
Number of change-over switches / for auxiliary contacts		0
Continuous current / of the auxiliary contact / rated value	A	10
Operating voltage / of the auxiliary contacts / for AC / maximum	V	500
Insulation voltage / of the auxiliary switch / rated value	V	500

Short-circuit:

Design of the fuse link / for short-circuit protection of the main circuit / necessary		fuse gL/gG: 160 A
Design of the fuse link / for short-circuit protection of the auxiliary switch / required		fuse gL/gG: 10 A

Installation/mounting/dimensions:

Type of mounting		floor mounting
• front mounting		Yes
• front mounting with central fixation		No

• front mounting with 4-hole fixation		No
• series installation		No
• Rail installation		No
Width	mm	112
Height	mm	169
Depth	mm	94

Connection type:

Design of the electrical connection / for main current circuit		connection terminals
Design of the electrical connection / for auxiliary contact		connection terminals
Type of the connectable conductor cross-section / for main contacts • finely stranded / with conductor end processing		150 mm ²
Type of connectable conductor cross section / for auxiliary contacts • solid • finely stranded / with conductor end processing • stranded		2x (0.75 to 2.5 mm ²), 1x 4 mm ² 2x (0.75 ... 1.5 mm ²), 1x 2.5 mm ² 2x (0.75 ... 2.5 mm ²), 1x 4 mm ²

Certificates/approvals:

Verification of suitability		UL / CSA
Conductor cross section that can be connected / for main contacts / solid / minimum	mm ²	16
Conductor cross section that can be connected / for main contacts / solid / maximum	mm ²	185
Conductor cross section that can be connected / for main contacts / stranded / minimum	mm ²	16
Conductor cross section that can be connected / for main contacts / stranded / maximum	mm ²	185
Conductor cross-section that can be connected / for main contacts / stranded wire / with conductor end processing / maximum	mm ²	150
Conductor cross-section that can be connected / for auxiliary contact / solid / minimum	mm ²	0.75
Conductor cross-section that can be connected / for auxiliary contact / solid / maximum	mm ²	4
Conductor cross-section that can be connected / for auxiliary contact / finely stranded / with conductor end processing / minimum	mm ²	0.75
Conductor cross-section that can be connected / for auxiliary contact / finely stranded / with conductor end processing / maximum	mm ²	2.5
Conductor cross section that can be connected / for auxiliary contacts / stranded / min.	mm ²	0.75
Conductor cross section that can be connected / for auxiliary contacts / stranded / max.	mm ²	4

Certificates/approvals:

General Product Approval



CCC



CSA



GOST



UL

Test Certificates

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

other

[Declaration of Conformity](#)

[Environmental Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3LD2318-1TL13/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD2318-1TL13

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Nov 1, 2012