

CIRCUIT BREAKER 230V 6KA, 1+N-POLE/1MW C10



Model	
Product brand name	SENTRON
Product designation	Miniature circuit breaker
Design of the product	Miniature circuit breaker compact
General technical data	
Number of poles / Note	1P+N
Tripping characteristic class	C
Mechanical service life (switching cycles) / typical	10 000
Overvoltage category	III
Degree of pollution	2
Supply voltage	
Type of voltage	AC
Operating current / at AC / rated value	10 A
Supply voltage	
• at AC / rated value	230 V
Operating voltage	
• minimum	24 V
• with single-phase operation / at AC / maximum	250 V

Supply voltage frequency / rated value	50/60 Hz
<b>Protection class</b>	
Protection class IP	IP20, with connected conductors
<b>Switching capacity</b>	
Switching capacity current	
• acc. to EN 60898 / rated value	6 kA
Energy limiting class	3
<b>Dissipation</b>	
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	1.3 W
<b>Product details</b>	
Product function / neutral conductor switching	Yes
Product feature / Touch protection	Yes
Product component	
• combined terminal top	No
• combined terminal bottom	No
Product feature	
• Properties for main switches in accordance with EN 60204-1	No
• halogen-free	Yes
• sealable	Yes
• silicon-free	Yes
Product extension / can be installed / supplementary devices	Yes
<b>Connections</b>	
Connectable conductor cross-section / solid	
• minimum	0.75 mm <sup>2</sup>
• maximum	16 mm <sup>2</sup>
Connectable conductor cross-section / stranded	
• minimum	0.75 mm <sup>2</sup>
• maximum	16 mm <sup>2</sup>
Connectable conductor cross-section / finely stranded / with core end processing	
• minimum	0.75 mm <sup>2</sup>
• maximum	10 mm <sup>2</sup>
Tightening torque [lbf·in] / with screw-type terminals	
• minimum	17.7 lbf·in
• maximum	22.1 lbf·in
Tightening torque / with screw-type terminals	
• minimum	2 N·m
• maximum	2.5 N·m

Position / of power supply cord	Any
---------------------------------	-----

### Mechanical Design

Height	90 mm
Width	18 mm
Depth	76 mm
Installation depth	70 mm
Number of width units	1
Mounting type	standard rail
Mounting position	any
Net weight	113.2 g

### Environmental conditions

Influence of the surrounding temperature	45°C, max. 95% humidity
Vibration resistance / acc. to IEC 60068-2-6	Yes
Ambient temperature	
• minimum	-25 °C
• maximum	45 °C
Ambient temperature / during storage	
• minimum	-40 °C
• maximum	75 °C
Number of test cycles / for environmental testing / acc. to IEC 60068-2-30	6

### Certificates

Reference code	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F

<b>General Product Approval</b>	<b>Declaration of Con- formity</b>	<b>other</b>
---------------------------------	--	--------------



CCC



IMQ



EG-Konf.

[Miscellaneous](#)

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SL6010-7>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5SL6010-7>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SL6010-7](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SL6010-7)

**Cx-Online-Generator**

<http://www.siemens.com/cax>



