



Hand-held scanners
IDM140 / IDM140 Bluetooth / general purpose /
cordless / Mid Range

IDM140-2PDFBT



Model Name > [IDM140-2PDFBT](#)
Part No. > [6036730](#)



At a glance

- Bluetooth wireless version for cordless applications with up to 30 m operating distance and integrated code buffer for code reading beyond 30 m
- Fast and reliable decoding even on poorly printed or partly damaged codes
- Large depth of field and reading distances of up to 600 mm
- Scan rate up to 500 scans/second
- Identification of codes with 0.076 mm module width
- Identification of all popular 1D codes, with PDF version also stacked codes

Your benefits

- Reliable identification reduces the need to manually input data
- High scanning speeds and aggressive reading performance increase productivity
- Highly dependable thanks to rugged housing and non-moving parts
- Its ergonomic design makes handling convenient and comfortable
- Greater flexibility - no cables
- One scanner reads standard range, high density and stacked codes



Features

Field of application:	Cordless, General purpose
Version:	Mid Range
Scanner design:	1D code hand-held scanner
Light source:	Visible red light (630 nm)
Code resolution:	≥0.076 mm
Reading distance (at code resolution):	50 mm ... 600 mm (0.5 mm)
Reading field (at distance):	150 mm (200 mm)
Scanning frequency:	≤ 500 Hz

Performance

Supported code type:	1D, Stacked
Bar code types:	Codabar, Code 11, Code 128, Code 32, Code 39, Code 93, German ITF Postal Code, Interleaved & Matrix 2 of 5, Limited/Expanded GS1 DataBar, Mainland China Postal Code, MSI/Plessey, Standard and Industrial 2 of 5, Telepen, UCC/EAN-128, UK/Plessey, UPC-A, UPC-E
Battery power:	Over 45,000 scans with full battery
Code buffer:	5000 Codes (EAN)

Interfaces

Serial:	✓
Function (Serial):	RS-232 TTL
Ethernet:	✓
Remark (Ethernet):	Optional via external connection module (CDM + CMF)
CAN bus:	✓
Remark (CAN bus):	Optional via external connection module (CAN232)
PROFINET:	-
PROFIBUS DP:	✓
Remark (PROFIBUS DP):	Optional via external connection module (CDF)
DeviceNet:	✓
Remark (DeviceNet):	Optional via external connection module (CDM + CMF)
PS/2:	✓
Function (PS/2):	Keyboard wedge
USB:	✓
Function (USB):	Keyboard wedge, COM-Port emulation
Bluetooth:	✓
Function (Bluetooth):	Wireless operating range up to 30 m (free view), batch function for expansion of the wireless radius, up to seven scanners communicate with one base station
Protocol (Bluetooth):	Bluetooth™ V2.1 EDR, 2.4 ... 2.4835 GHz
Optical indicators:	2 LEDs (good read, charge of battery , radio connection status)
Acoustic indicators:	Beeper, disengageable (good read)
Vibration:	No

Mechanics/electronics

Operating voltage:	5 V± 5 %
Power consumption:	Operation: Typ. 180 mA, Standby: Typ. 80 mA
Housing color:	Black/gray
Enclosure rating:	IP 41
Weight:	230 g, incl. rechargeable battery
Dimensions:	97.8 mm x 70.5 mm x 156.2 mm


Ambient data

Shock resistance:	25 drops From 1.8 m height on concrete
Ambient operating temperature:	0 °C ... 50 °C
Storage temperature:	-40 °C ... 70 °C
Permissible relative humidity:	± 95 %, non-condensing
Ambient light safety:	100,000 lx

General notes

Items supplied:	Cordless scanner and battery is included in delivery
-----------------	--

Code resolution in mm (mil)



Australia

Phone +61 3 9457 0600
1800 334 802 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail sac@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Ceská Republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail kundenservice@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6801000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 3358 1341
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederlands

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail austefjord@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail admin@sicksgp.com.sg

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886-2-2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 8865 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com