



## Incremental encoders DDS50

DDS50E-S4GT02048



**Model Name** > **DDS50E-S4GT02048**  
**Part No.** > **1038776**



*Illustration may differ*

**At a glance**

- Compact diameter of 50 mm
- Choice of various electric interfaces: TTL/RS-422, HTL/push pull and open collector NPN
- Face mount flange with solid shaft
- Connection type using axial cable outlet
- Line counts from 100 up to 2,500 possible
- Working temperature range: -10 °C ... 70 °C
- Enclosure rating: IP65

**Your benefits**

- Compact design easily fits in applications with limited installation space
- Extensive incremental encoders product portfolio means users can select the right solution for their requirements
- Excellent price-performance ratio with a rugged IP 65 enclosure rating



**Performance**

Error limits:	$\pm 0.01^\circ$
Measuring step deviation:	$\pm 0.004^\circ$ <sup>1)</sup>
Measuring step:	$0.04^\circ$ <sup>2)</sup>
Pulses per revolution:	2,048

<sup>1)</sup> Measuring step x 0.1 <sup>2)</sup>  $360^\circ / (\text{number of lines} \times 4)$

**Mechanical data**

Mechanical interface:	Solid shaft, Face mount flange
Shaft diameter:	8 mm x 15.5 mm
Mass:	145 g
Start up torque:	1 Ncm (20 °C)
Operating torque:	4 Nmm (20 °C)
Maximum operating speed:	6,000 U/min <sup>1)</sup>
Moment of inertia of the rotor:	0.8 kg/mm <sup>2</sup>
Bearing lifetime:	2 x 10 <sup>9</sup> revolutions
Max. angular acceleration:	5 x 10 <sup>5</sup> rad/s <sup>2</sup>
Permissible shaft loading radial/axial:	50 N, 30 N

<sup>1)</sup> Self-warming 3.3 K per 1,000 1/min

## Electrical data

---

Electrical interface:	7 V ... 24 V, HTL/Push pull, Cable, axial, 5 m
Connection type:	Cable, axial, 5 m
Operating power consumption (no load):	100 mA
Supply voltage:	7 V ... 24 V
Output current:	20 mA
Maximum output frequency:	300 kHz
Reference signal, number:	1
Reference signal, position:	90 °, electronically, gated with A and B

## Ambient data

---

EMC:	EN 61000-6-2, EN 61000-6-4
Protection class housing side with cable outlet:	IP 65
Protection class shaft side:	IP 65
Air humidity:	90 % <sup>1)</sup>
Working temperature range:	-10 °C ... 70 °C
Storage temperature range:	-25 °C ... 85 °C, without package
Resistance to shocks:	100 g, 6 ms (EN 60068-2-27)
Resistance to vibration:	5 g, 10 Hz ... 200 Hz (EN 60068-2-6)
Enclosure rating:	IP 65

<sup>1)</sup> Condensation of the optical scanning not permitted

**Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Ceská Republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail kundenservice@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederlands**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail admin@sicksgp.com.sg

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)