



**Inductive sensor
magnetic field immune
NI2-Q9,5-AP6/S34**



- Rectangular, height 9.5 mm
- Active face, lateral
- Plastic, PP GR-20
- Magnetic field immune (weld-resistant) to DC and AC fields
- 3-wire DC, 10...30 VDC
- NO contact, PNP output
- Cable connection

Wiring diagram



Functional principle

Inductive sensors detect metal objects contactless and wear-free. For this purpose they use a high-frequency electromagnetic AC field that interacts with the target. The sensors hosting a ferrite core coil generate the AC field through an LC resonant circuit. Magnetic field sensors incorporate a special ferrite core making them immune to magnetic AC and DC fields. Hence, they can be applied in welding systems.

Type code	NI2-Q9,5-AP6/S34
Ident no.	1650077
Rated operating distance Sn	2 mm
Mounting condition	non-flush
Assured sensing range	≤ (0,81 x Sn) mm
Correction factors	St37 = 1; Al = 0.3; stainless steel = 0.7; Ms = 0.4
Repeatability	≤ 2 % of full scale
Temperature drift	10 %
Hysteresis	3...15 %
Ambient temperature	-25...+70 °C
Operating voltage	10...30VDC
Residual ripple	≤ 10 % U _{ss}
DC rated operational current	≤ 150 mA
No-load current I ₀	≤ 15 mA
Residual current	≤ 0.1 mA
Rated insulation voltage	≤ 0.5 kV
Short-circuit protection	yes/ cyclic
Voltage drop at I ₀	≤ 1.8 V
Wire breakage / Reverse polarity protection	yes/ complete
Output function	3-wire, NO contact, PNP
Switching frequency	1 kHz
Design	rectangular, Q9.5
Dimensions	20 x 17 x 9.5 mm
Housing material	plastic, PP
Connection	cable
Cable quality	2 mm, grey, Lif9Y-11Y, PUR, 2 m
Cable cross section	3 x 0.08 mm ²
Litz wire	40x0.05mm ²
Vibration resistance	55 Hz (1 mm)
Shock resistance	30 g (11 ms)
Protection class	IP67
MTTF	2283 years acc. to SN 29500 (Ed. 99) 40 °C

**Inductive sensor
magnetic field immune
NI2-Q9,5-AP6/S34**

Distance W	3 x Sn
Distance S	5 x Sn
Distance G	6 x Sn
Distance N	2 x Sn

Width of the active face B 9.5 mm

