



- Rectangular, height 25 mm
- Sensor housing, GD-CuZn 12
- Duroplast front cap, very resistant to thermal and mechanical load
- 4 selectable connector positions
- Rigid sensor head
- Factor 1 for all metals
- Resistant to magnetic fields
- Extended temperature range
- High switching frequency
- Auto-compensation protects against pre-attenuation
- 3-wire DC, 10...30 VDC
- NO contact, PNP output
- Male M8 x 1

Type code	NI15U-CA25-AP6X2-V1131
Ident no.	1625642
Rated operating distance Sn	15 mm
Mounting condition	non-flush, partially embeddable
Assured sensing range	≤ (0,81 x Sn) mm
Repeatability	≤ 2 % of full scale
Temperature drift	10 %
	≤ ± 15 %, ≤ -25 °C v ≥ +70 °C
Hysteresis	3...15 %
Ambient temperature	-30...+85 °C
Operating voltage	10...30VDC
Residual ripple	≤ 10 % U _{ss}
DC rated operational current	≤ 200 mA
No-load current I ₀	≤ 15 mA
Residual current	≤ 0.1 mA
Rated insulation voltage	≤ 0.5 kV
Short-circuit protection	yes/ cyclic
Voltage drop at I ₀	≤ 1.8 V
Wire breakage / Reverse polarity protection	yes/ complete
Output function	3-wire, NO contact, PNP
Protection class	□
Switching frequency	0.25 kHz
Design	rectangular, CA25
Dimensions	40 x 25 x 25 mm
	variable orientation of active face in 5 directions
Housing material	metal, GD-CuZn 12
Connection	male, M8 x 1
Vibration resistance	55 Hz (1 mm)
Shock resistance	30 g (11 ms)
Protection class	IP67
MTTF	874 years acc. to SN 29500 (Ed. 99) 40 °C
Power-on indication	LED green
Switching state	LED yellow

Wiring diagram



Functional principle

Inductive sensors detect metal objects contactless and wear-free. Due to the patented multicore system, uprox®+ sensors have distinct advantages over conventional sensors. They detect all metals at the same large switching distance and are resistant to magnetic fields.

**Inductive sensor
NI15U-CA25-AP6X2-V1131**

Distance W	3 x Sn
Distance T	4 x Sn
Distance S	0.5 x B
Distance G	6 x Sn
Distance N	1 x B
<hr/>	
Width of the active face B	25 mm

1-side flush mounting possible:
1-side flush mounting: $S_r = 15 \text{ mm}$
(min. front cap protrusion 8 mm)



Wiring accessories

Type code	Ident no.	Description	Dimension drawing
PKG3M-2/TEL	6625058	Connection cable, female M8, straight, 3-pin, cable length: 2 m, sheath material: PVC, black; cULus approval; other cable lengths and qualities available, see www.turck.com	