

- Threaded barrel, M18 x 1
- Brass, PTFE-coated
- Factor 1 for all metals
- Protection class IP68
- Resistant to magnetic fields
- High switching distance
- Integrated protection against pre-attenuation
- Little metal-free spaces
- 3-wire DC, 10...30 VDC
- NO contact, PNP output
- Male M12 x 1

Type code NI15U-MT18-AP6X-H1141
Ident no. 1635333


Rated operating distance Sn 15 mm
Mounting condition non-flush
Assured sensing range $\leq (0,81 \times S_n)$ mm
Repeatability $\leq 2\%$ of full scale
Temperature drift $\leq \pm 15\%$, $\leq -25\text{ °C}$ v $\geq +70\text{ °C}$
Hysteresis 3...15 %
Ambient temperature -30...+85 °C

Operating voltage 10...30VDC
Residual ripple $\leq 10\%$ U_{ss}
DC rated operational current ≤ 200 mA
No-load current I_0 ≤ 15 mA
Residual current ≤ 0.1 mA
Rated insulation voltage ≤ 0.5 kV
Short-circuit protection yes/ cyclic
Voltage drop at I_0 ≤ 1.8 V
Wire breakage / Reverse polarity protection yes/ complete
Output function 3-wire, NO contact, PNP
Protection class \square
Switching frequency 1.5 kHz

Design threaded barrel, M18 x 1
Dimensions 52 mm
Housing material metal, CuZn, PTFE-coated
Material active area Plastic, LCP, PTFE-coated
Max. tightening torque housing nut 15 Nm
Connection male, M12 x 1
Vibration resistance 55 Hz (1 mm)
Shock resistance 30 g (11 ms)
Protection class IP68
MTTF 874 years acc. to SN 29500 (Ed. 99) 40 °C

Switching state LED yellow

Wiring diagram



Functional principle

Inductive sensors detect metal objects contactless and wear-free. Due to the patented multi-coil system, *uprox*+ sensors have distinct advantages over conventional sensors. They excel in largest switching distances, maximum flexibility and operational reliability as well as efficient standardization.

Distance D	72 mm
Distance W	45 mm
Distance T	54 mm
Distance S	27 mm
Distance G	90 mm
Distance N	20 mm



Diameter of the active area B \varnothing 18 mm



All non-flush mountable *uprox⁺* threaded barrel sensors can be screwed to the upper edge of the barrel. Thus safe operation is guaranteed with a reduced switching distance of max. 20 %.

When installed in an aperture plate a distance of X = 70 mm must be observed.

Accessories

Type code	Ident no.	Description	Dimension drawing
BST-18B	6947214	Fixing clamp for threaded barrel devices, with dead-stop; material: PA6	 <p>Technical drawing of a rectangular fixing clamp. Dimensions: length 40, width 30, height 24. A circular hole with diameter $\phi 18$ is on the front face. Two slots are on the top surface. An M5 screw is shown passing through the top. A dead-stop is indicated on the right side.</p>
BSS-18	6901320	Mounting bracket for smooth and threaded barrel devices; material: Polypropylene	 <p>Technical drawing of a rectangular mounting bracket. Dimensions: length 40.5, width 30, height 32. A circular hole with diameter $\phi 18$ is on the front face. Two slots are on the top surface. A 5mm hole is on the top edge.</p>