



**ultrasonic sensor  
diffuse mode sensor  
RU100-Q30-LUX-H1141**




- Operating voltage 18...35 VDC
- Upper analog value adjustable via potentiometer
- Analog output, 0...10 V
- Display for object detection
- synchronizable
- opening angle of sonic cone 6°

**Wiring diagram**



**Functional principle**

Ultrasonic sensors use ultrasonic waves for non-contact and wear-free detection of many objects. Regardless of whether the object is transparent or opaque, metallic or non-metallic, or of liquid, solid or powdery consistency. Even environmental conditions such as spray, dust or rain hardly affect their function.



<b>Type code</b>	RU100-Q30-LUX-H1141
Ident no.	1820205
<b>Design</b>	rectangular, Q30
Housing material	plastic, Crastin, SK645FR
Sonic converter material	plastic, Epoxy-resin
Connection	male, M12 x 1, 4-wire
Protection class	IP65
Ambient temperature	0...+55 °C
<b>Switching state</b>	LED
<b>Operating voltage</b>	18...35VDC
No-load current I <sub>0</sub>	≤ 35 mA
Load resistance	≤ 1000 Ω
Response time	90 ms
Voltage output	0...10V
Short-circuit protection	yes/ cyclic
Reverse polarity protection	complete
Wire breakage protection	yes
<b>Range</b>	20...100 cm
Ultrasound frequency	230 kHz
Repeatability	≥ ± 1.5 mm
Edge lengths of the nominal actuator	20 mm
Approach speed	≤ 8 m/s
Pass speed	≤ 1.5 m/s

ultrasonic sensor  
diffuse mode sensor  
RU100-Q30-LUX-H1141

**Wiring accessories**

Type code	Ident no.	Description	Dimension drawing
RKC4.4T-2/TEL	6625013	Connection cable, female M12, straight, 4-pin, cable length: 2 m, sheath material: PVC, black; cULus approval; other cable lengths and qualities available, see <a href="http://www.turck.com">www.turck.com</a>	
WKC4.4T-2/TEL	6625025	Connection cable, female M12, angled, 4-pin, cable length: 2 m, sheath material: PVC, black; cULus approval; other cable lengths and qualities available, see <a href="http://www.turck.com">www.turck.com</a>	