


**Photoelectric sensor**  
**diffuse mode sensor with fixed-field background suppression**  
**T18SP6FF50**

- Cable, 2 m
- Protection class IP67
- Ambient temperature: -40...+70 °C
- Operating voltage: 10...30 VDC
- PNP switching output, changeover

**Wiring diagram**





**Functional principle**

The emitter and receiver are incorporated in a single housing. The light reflection of the target is detected and triggers the sensor to switch. Thus the switching distance largely depends on the reflectivity of the target.

**Excess gain curve**




Excess gain in relation to the distance



<b>Type code</b>	T18SP6FF50
Ident no.	3032470
<b>Operating mode</b>	diffuse mode sensor with fixed-field background suppression
Light type	IR
Wavelength	880 nm
Range	0...50 mm
Ambient temperature	-40...+70 °C
<b>Operating voltage</b>	10...30VDC
No-load current I <sub>0</sub>	≤ 35 mA
Short-circuit protection	yes/ cyclic
Reverse polarity protection	yes
Output function	connection programmable, PNP
Switching frequency	≤ 160 Hz
Readiness delay	≤ 100 ms
Overcurrent release	> 220 mA
<b>Design</b>	cylindrical/threaded, T18
Dimensions	30 x 30 x 41.5 mm
Housing material	plastic, PBT
Lens	plastic, acrylic
Connection	cable
Cable length	2 m
Cable cross section	4 x 0.5 mm <sup>2</sup>
Protection class	IP67
MTTF	448 years acc. to SN 29500 (Ed. 99) 40 °C
<b>Power-on indication</b>	LED green
Switching state	LED yellow
Error indication	LED green flashing
Alarm display	LED yellow flashing

**Photoelectric sensor  
diffuse mode sensor with fixed-field background suppression  
T18SP6FF50**

**Accessories**

Type code	Ident no.	Description	Dimension drawing
SMB1815SF	3053279	Mounting bracket, PBT black, for PICO-GUARD points	 <p>Technical drawing showing dimensions for the SMB1815SF mounting bracket: 11.7, 50.8, 43.2, 25.4, 36.1, 0.5, 0.5, 0.5.</p>
SMB18A	3033200	Mounting bracket, stainless steel, for sensors with 18 mm thread	 <p>Technical drawing showing dimensions for the SMB18A mounting bracket: 32, 18.5, 4.6 wide, 4.5, 25.4, 41, 7.6, R 24.2, 46.</p>
SMB18FM	3079421	mounting bracket, black, M22 x1.5 mm, male thread, female thread M18 x 1, for sensors with 18 mm thread	
SMBAMS18P	3073134	Mounting bracket, stainless steel, for sensors with 18 mm thread	 <p>Technical drawing showing dimensions for the SMBAMS18P mounting bracket: 6.53, 19, 32, 16, 45, 23, 74, 17, 34, 2.0.</p>