

measuring light screen
receiver
BMRL4832A

TURCK

Industrial
Automation



- Minimum target size 9.7 mm
- Scan field 1200 mm
- max. sensing range 4.6 m
- Operating voltage 11.8...12.2 VDC (from controller)
- Protection class IP65
- adjustment via software

Zasada działania

Measuring light screens are ideally suited for precise detection and inspection tasks such as product profiling, sizing, edge and centre guiding, hole and parts detection and the like. Each system consists of an emitter, receiver and a controller module, which is equipped with several switching and analogue outputs, depending on the specific version. The device also enables data transmission via RS232 or R485, either in a binary or ASCII code format. The scan times depend on the height of the measuring array and the adjusted scan mode. Detailed information can be taken from the instruction manual.

Typ	BMRL4832A
Nr kat.	3038536
Tryb pracy	kurtyna świetlna
Optical resolution	9.7 mm
Max zakres wykrywania	600...4600 mm
Detection zone height	1200 mm
Temperatura pracy	-20...+70 °C
Napięcie zasilania	11.4...14VDC
Prąd bez obciążenia I ₀	≤ 1200 mA
Wykonanie	prostokątnościenna, Mini Array
Wymiary	38.1 x 38.1 x 1267 mm
Materiał obudowy	metal, AL
Soczewka	tworzywo sztuczne, acrylic
Podłączenie	złącze, 7/8"
Stopień ochrony	IP65