

measuring light screen
emitter
BMEL7232A

TURCK

Industrial
Automation



- Minimum target size 9.7 mm
- Scan field 1810 mm
- max. sensing range 4.6 m
- Operating voltage 11.8...12.2 VDC (from controller)
- Protection class IP65
- adjustment via software

Functional principle

Measuring light screens are ideally suited for precise detection and inspection tasks such as product profiling, sizing, edge and centre guiding, hole and parts detection and the like. Each system consists of an emitter, receiver and a controller module, which is equipped with several switching and analogue outputs, depending on the specific version. The device also enables data transmission via RS232 or R485, either in a binary or ASCII code format. The scan times depend on the height of the measuring array and the adjusted scan mode. Detailed information can be taken from the instruction manual.

Type code	BMEL7232A
Ident no.	3038539
Operating mode	light screen
Light type	IR
Wavelength	880 nm
Optical resolution	9.7 mm
Range	600...4600 mm
Detection zone height	1810 mm
Ambient temperature	-20...+70 °C
Operating voltage	11.4...14VDC
No-load current I ₀	≤ 1200 mA
Design	rectangular, Mini Array
Dimensions	38.1 x 38.1 x 1877 mm
Housing material	metal, AL
Lens	plastic, acrylic
Connection	male, 7/8"
Protection class	IP65