

measuring light screen  
receiver  
MAHR70A

**TURCK**

Industrial  
Automation



- Minimum target size 2.5 mm
- Scan field 1788 mm
- max. sensing range 1.8 m
- Operating voltage 11.8...12.2 VDC (from controller)
- Protection class IP65
- adjustment via software

**Zasada działania**

Measuring light screens are ideally suited for precise detection and inspection tasks such as product profiling, sizing, edge and centre guiding, hole and parts detection and the like. Each system consists of an emitter, receiver and a controller module, which is equipped with several switching and analogue outputs, depending on the specific version. The device also enables data transmission via RS232 or R485, either in a binary or ASCII code format. The scan times depend on the height of the measuring array and the adjusted scan mode. Detailed information can be taken from the instruction manual.

<b>Typ</b>	MAHR70A
Nr kat.	3062672
<b>Tryb pracy</b>	kurtyna świetlna
Optical resolution	2.5 mm
Max zakres wykrywania	380...1800 mm
Detection zone height	1788 mm
Temperatura pracy	0...+50 °C
<b>Napięcie zasilania</b>	11.4...14VDC
<b>Wykonanie</b>	prostopadłościenna, Mini Array
Wymiary	38.1 x 38.1 x 1865 mm
Materiał obudowy	metal, AL
Soczewka	tworzywo sztuczne, acrylic
Podłączenie	złącze, 7/8"
Stopień ochrony	IP65