



- Mobile reading and writing of RFID data carriers
- Handheld with HF antenna
- Incl. TURCK RFID software for reading and writing of data
- Display of decimal, binary, hexadecimal and ASCII codes
- With RS232 interface
- Fold-out antenna
- Protection class IP65
- Incl. docking station with power supply

Type code	PD-IDENT
Ident no.	1542331
Ambient temperature	-20...+50 °C
Data transfer	inductive coupling
Operating frequency	13.56 MHz
Radio communication and protocol standards	ISO 15693
Device features	XScale, 624 MHz
Speicher	512MB Flash ROM; 128MB RAM
Display	3.5", 320 x 240, Touchscreen
Keyboard	45 Keys
Battery capacity	1650 mAh
Included software	Turck RFID software, SDK available as free download
Operating system	WinCE
Dimensions	250x 120.7x 60.2mm
Housing material	plastic, yellow
Protection class	IP65
Packaged quantity	1

Accessories

Type code	Ident no.	Description	Dimension drawing
PD-IDENT-PF	1542336	protective film (25 pcs.)	Kein Maßbild vorhanden/ No dimension drawing available
PD-IDENT-DS	1542333	docking station, incl. power supply, RS232 cable	Kein Maßbild vorhanden/ No dimension drawing available
PD-IDENT-BC	1542335	battery charger	Kein Maßbild vorhanden/ No dimension drawing available
PD-IDENT-RS	1542338	replacement pins (25 pcs.)	Kein Maßbild vorhanden/ No dimension drawing available
PD-IDENT-CB	1542334	carry case	Kein Maßbild vorhanden/ No dimension drawing available
PD-IDENT-RB-2300	7030584	Replacement battery PD-IDENT with 2300 mAh	