



- For roller conveyors
- Rectangular, 400 x 80 mm, height 25 mm
- Active face on top
- Plastic, PBT-GF30-V0
- Every read/write head can communicate with a number of different TURCK data carriers.
- Powered and operated only via BL ident interface module
- Male M12 x 1, only for use with BL ident extension cable

Connectors .../S2500



Functional principle

The HF read/write heads operating at a frequency of 13.56 MHz form a transmission zone the size of which (0...500 mm) varies, depending on the combination of read/write head and data carrier.

The read/write distances mentioned here only represent standard values measured under laboratory conditions.

The read/write distances of the data carriers for mounting in metal TW-R**-M(MF) were determined in metal.

Attainable distances may vary by up to 30 % due to component tolerances, mounting conditions, ambient conditions and material qualities (especially when mounted in metal)

Testing of the application under real operating conditions is therefore essential, especially with read/write on-the-fly!

Type code	TNLR-Q80L400-H1147L
Ident no.	7030234Lengthwise
Mounting condition	non-flush, flush mountable
Ambient temperature	-25...+70 °C
Operating voltage	19.2...28.8VDC
DC rated operational current	≤ 230 mA
Data transfer	inductive coupling
Operating frequency	13.56 MHz
Radio communication and protocol standards	ISO 15693
Read/write distance max.	360 mm
Output function	4-wire, read/write
Design	rectangular
Dimensions	400x 80x 25mm
Housing material	plastic, PBT, black
Material active area	Plastic, Black
Connection	male, M12 x 1
Vibration resistance	55 Hz (1 mm)
Shock resistance	30 g (11 ms)
Protection class	IP67
MTTF	121 years acc. to SN 29500 (Ed. 99) 40 °C
Power-on indication	LED green
Packaged quantity	1
Special features	For roller conveyors (vertical or horizontal orientation)