



- The high-temperature data carriers must undergo adequate stress tests within the proposed temperature processes before deployment. Otherwise, their durability cannot be guaranteed when exposed to temperatures outside the denoted range.
- EEPROM, memory 112 byte
- TID serial number: 8 byte
- Only for direct mounting on metal

Functional principle

The UHF read/write heads form an air interface the size of which may vary, depending on the combination of read/write head and data carrier.

The read/write distances mentioned here only represent standard values measured under laboratory conditions and free from any influences caused by materials.

Attainable distances may vary due to component tolerances, mounting conditions, ambient conditions and material qualities, especially when mounted in metal.

Testing of the application under real operating conditions is therefore essential, especially with read/write on-the-fly!

Type code	TW865-868-Q22L36-M-HT-B112
Ident no.	7030450
Data transfer	alternating electromagnetic field
Operating frequency	865...868 MHz
Memory type	EEPROM
Chip	Alien Higgs 3
Memory	112 byte
Memory	read/write
Freely usable memory	64 byte
EPC memory	12 byte
Number of read operations	unlimited
Number of write operations	10 ⁵
Typical read time	2 ms/byte
Typical write time	3 ms/byte
Radio communication and protocol standards	ISO 18000-6C EPCglobal Gen 2
Minimum distance to metal	0 mm
Ambient temperature	-40...+85 °C
Housing length	36 mm mm
Housing width	22 mm mm
Housing height	7 mm mm
Housing material	plastic
Material active area	Plastic, Black, TPE
Protection class	IP67
Packaged quantity	1
Special features	High-temperature, for direct mounting on metal