



- Mobile reading and writing of RFID data carriers
- Handheld with UHF antenna
- Microsoft Windows CE 5
- Customized software solution on request
- Bluetooth
- Protection class IP65
- Incl. docking station with power supply, USB cable
- Optionally available on request: Handheld (1D / 2D imager or 1D laser)
- Optionally available on request: WLAN, 4400 mAh battery and software development kit (SDK)

<b>Type code</b>	PD-IDENT-UHF-RBTW-920-925
Ident no.	7030532
<b>Ambient temperature</b>	-20...+50 °C
<b>Data transfer</b>	alternating electromagnetic field
Operating frequency	920...925 MHz
Radio communication and protocol standards	ISO 18000-6C EPCglobal Gen 2
Output power	500 mW (ERP), adjustable
Antenna polarization	linear horizontal
<b>Device features</b>	XScale, 624 MHz
Speicher	1GB Flash ROM; 256MB RAM
Display	3.7", 480 x 640, Touchscreen
Keyboard	55 Keys
Battery capacity	3300 mAh
<b>Communication via</b>	Bluetooth Class II
<b>Included software</b>	OEM demo software, SDK available as free download
Operating system	WinCE
<b>Docking station connection type</b>	USB (serial)
<b>Dimensions</b>	260x 100x 42mm
Housing material	plastic, black
<b>Protection class</b>	IP65
<b>Packaged quantity</b>	1

**Accessories**

Type code	Ident no.	Description	Dimension drawing
PD-IDENT-TW-ETHER-NET	7030544	Ethernet adapter cable	
PD-IDENT-TW-RS232	7030554	RS232 adapter cable	
PD-IDENT-TW-3300	7030517	Replacement battery 3300 mAh	
PD-IDENT-TW-4400	7030518	Replacement battery 4400 mAh	
PD-IDENT-TW-STYLUS	7030550	replacement pens (25 pcs.)	
PD-IDENT-TW-STYLUS-HOLDER-KIT	7030549	pen holder	
PD-IDENT-TW-POUCH	7030548	Carry case	