

SIMATIC Field PG M6 Advanced; i7-8850H (2.6 to 4.3 GHz; 6 kernels + hyper-threading; 9 MB Smart Cache); 15.6" display; Full HD (1920x 1080); WLAN 802.11ac & Bluetooth V5.0; DVD +/-RW; UHD Graphics 630; 1x 16 GB DDR4 SD-RAM SO-DIMM; 256 GB SSD SATA (2.5"); without S5 interface, without S5-EPROMMER Line cable with power plug; USA; Keyboard: QWERTZ/QWERTY; without NVME (M.2); Windows 10 Enterprise (Version 1903), 64-bit; License for STEP 7 Professional Combo (V16 & 2017 SR1); WinCC Advanced Combo (V16 & WinCC flex. 2008 SP5); Safety Advanced Combo (V16 & Distr. Safety 5.4 SP5); SINEMA RC Client 2.0; Version of software V16.0.0.0

### General information

Design of the programming device	Notebook
----------------------------------	----------

### Display

Design of display	15.6" full HD display in 16:9 format
-------------------	--------------------------------------

#### Resolution (pixels)

- |                               |             |
|-------------------------------|-------------|
| • Horizontal image resolution | 1 920 Pixel |
| • Vertical image resolution   | 1 080 Pixel |

#### General features

- |                  |                       |
|------------------|-----------------------|
| • Non-reflecting | Yes                   |
| • Luminance      | 300 cd/m <sup>2</sup> |

#### Backlighting

- |                        |     |
|------------------------|-----|
| • Type of backlighting | LED |
|------------------------|-----|

### Control elements

#### Keyboard fonts

- |          |   |
|----------|---|
| • Design | QWERTZ/QWERTY or AZERTY (French); 87 keys |
|----------|---|

#### Touch operation

- |                        |               |
|------------------------|---------------|
| • Integrated touch pad | Yes; Clickpad |
|------------------------|---------------|

### Supply voltage

Design of the power supply	External wide-range power supply; 3-pole
----------------------------	--

permissible range, lower limit (AC)	100 V; ±10 %, sinusoidal
-------------------------------------	--------------------------

permissible range, upper limit (AC)	240 V; ±10 %, sinusoidal
-------------------------------------	--------------------------

#### Line frequency

- |                                  |       |
|----------------------------------|-------|
| • permissible range, lower limit | 47 Hz |
| • permissible range, upper limit | 63 Hz |

### Processor

Processor type	Intel Core i5-8400H (2.5 to 4.2 GHz, 4 cores and hyper-threading, 8 MB Smart Cache) or i7-8850H (2.6 to 4.3 GHz 6 cores and hyper-threading, 9 MB Smart Cache)
Chipset	Intel CM246
Hyper-threading	Yes
Turbo Boost Technology 2.0	Yes

### Graphic

Graphics controller	Intel® UHD Graphics 630
---------------------	-------------------------

### Drives

SSD	Yes; Easy to replace
<ul style="list-style-type: none"> <li>• Memory capacity</li> </ul>	256 Gbyte; Up to 2 TB SSD
TPM Security Chip	Yes; 2.0 (version for China without TPM)

### Memory

Type of memory	DDR4-SDRAM SO-DIMM
Work memory	
<ul style="list-style-type: none"> <li>• Number of slots</li> </ul>	2; Can be equipped with 1x 8 GB, 1x 16 GB or 2x 16 GB

### Accumulator

Replaceable	Yes; Lithium-ion battery
Capacity	8.25 A·h

### Interfaces

Number of interfaces PROFIBUS DP	1; 1x PROFIBUS DP / MPI; 9-pin Sub-D socket; 9.6 kBaud to 12 MBaud
Number of RS 232 interfaces	1; 25-pin socket
Number of USB interfaces	4
<ul style="list-style-type: none"> <li>• Type A</li> </ul>	3; 1x USB port incl. integrated charging function for USB devices (e.g. smartphone) - also with device switched off
<ul style="list-style-type: none"> <li>• Type C</li> </ul>	1; USB 3.1 Gen. 2
Number of chip-card readers	1; Smart Card Reader (ISO/IEC 7816)
Bluetooth radio standard	Yes; V5.0
Multimedia card/SD card slot	2 in 1 (SDHC UHS-II, MMC)
Card reader for SIMATIC memory cards	SIMATIC memory cards (for S7-300/400), SMC (for S7-1x00), SIMATIC micro memory card (for S7-300/C7/ET 200) - including programming interfaces
Universal Audio Jack	Yes; Audio socket for 3.5 mm jack

### Video interfaces

<ul style="list-style-type: none"> <li>• analog video signal (VGA)</li> </ul>	Yes; via adapter from DVI to VGA
<ul style="list-style-type: none"> <li>• DVI-I</li> </ul>	Yes; 1x
<ul style="list-style-type: none"> <li>• DisplayPort</li> </ul>	Yes; 1x

### Industrial Ethernet

<ul style="list-style-type: none"> <li>• Industrial Ethernet interface</li> </ul>	2x Ethernet (RJ45)
<ul style="list-style-type: none"> <li>— 100 Mbps</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— 1000 Mbps</li> </ul>	Yes

• Wake on LAN	Yes
• IAMT (Intel Active Management Technology)	Yes
<b>WLAN</b>	
• Type	802.11ac
<b>Interrupts/diagnostics/status information</b>	
LED status display	Battery status, device status, access to HDD/DVD, access to SD/MMC, MPI/DP, S5 and S7 modules / Card Reader (except Smart Card Reader), Num Lock, Caps Lock, WLAN active
<b>EMC</b>	
<b>Interference immunity against discharge of static electricity</b>	
• Interference immunity against discharge of static electricity acc. to IEC 61000-4-2	Yes; $\pm 4$ kV contact discharge acc. to IEC 61000-4-2, ESD; $\pm 8$ kV air discharge acc. to IEC 61000-4-2, ESD
<b>Interference immunity to cable-borne interference</b>	
• Interference immunity on supply cables	$\pm 2$ kV (according to IEC 61000-4-4, burst); $\pm 1$ kV (according to IEC 61000-4-5, surge pulse/line to line); $\pm 2$ kV (according to IEC 61000-4-5, surge pulse/line to ground)
• Interference immunity on signal cables	$\pm 1$ kV (according to IEC 61000-4-4, burst, length < 30 m); $\pm 2$ kV (according to IEC 61000-4-4, burst, length > 30 m); $\pm 2$ kV (according to IEC 61000-4-5, surge sym./line to ground, length > 30 m)
<b>Standards, approvals, certificates</b>	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
DIN/ISO 9001	Yes
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• min.	5 °C; Max. 10 °C/h (no condensation)
• max.	40 °C; Max. 10 °C/h (no condensation)
<b>Ambient temperature during storage/transportation</b>	
• min.	-20 °C; Max. 20 °C/h (no condensation)
• max.	60 °C; Max. 20 °C/h (no condensation)
<b>Relative humidity</b>	
• Operation, min.	5 %; At 30 °C/h (no condensation); Tested according to IEC 60068-2-78, IEC 60068-2-30, IEC 60068-2-14
• Operation, max.	85 %; At 30 °C/h (no condensation); Tested according to IEC 60068-2-78, IEC 60068-2-30, IEC 60068-2-14
<b>Vibrations</b>	
• Operation, tested according to IEC 60068-2-6	Yes
<b>Shock testing</b>	
• tested according to IEC 60068-2-27	Yes
<b>Operating systems</b>	

Local language of operating system	Multi-Language User Interface (MUI): 6 languages (English, German, French, Spanish, Italian, Chinese)
<b>pre-installed operating system</b>	
• Windows 10	Yes; Windows 10 Enterprise 64-bit
<b>Software</b>	
<b>Preinstalled</b>	
• STEP 7 Professional (TIA Portal)	Yes; Software version: V15.1
• STEP 7	Yes; Professional 2017 SR1
• WinCC flexible Advanced 2008	Yes; Software version: SP5
• WinCC Advanced (TIA Portal)	Yes; Software version: V15.1
• STEP 5	Yes; Optional; software version: STEP 5 V7.23 HF2 (incl. GRAPH 5/II V7.15)
<b>Mechanics/material</b>	
Material of housing	metal
Handle	Yes; retractable
Socket for Kensington lock	Yes
rubber corner guards	Yes
<b>Dimensions</b>	
Width	385 mm
Height	53 mm
Depth	275 mm
<b>Weights</b>	
Weight, approx.	3.4 kg; incl. rechargeable battery
<b>Scope of supply</b>	
Accumulator	Yes
Power supply	Yes
Backpack	Yes
SIMATIC Software	Yes
Recovery media	Yes; Restore & Recovery
<b>Other</b>	
free hotline	Yes
Note:	Made in Germany: development and production in Germany
<b>last modified:</b>	10/30/2020