SIEMENS

Product data sheet 3RT2916-1BB00



SURGE SUPPRESSOR, VARISTOR, AC 24...48V, DC 24...70V, F. CONT. RELAYS A. MOTOR CONT. SZ S00,

General technical data:				
product brand name		SIRIUS		
product designation		surge suppressor		
Size of the contactor		S00		
Design of the surge suppressor		with varistor		
Ambient temperature				
during storage	°C	-40 +80		
during operating	°C	-25 +60		

Control circuit:				
Type of voltage / of the controlled supply voltage		AC/DC		
Control supply voltage frequency				
• 1 / rated value	Hz	50		
• 2 / rated value	Hz	60		
Control supply voltage / 1				
• for DC				
initial rated value	V	24		
• final rated value	V	70		
• at 50 Hz / for AC				
initial rated value	٧	24		
• final rated value	V	48		

• at 60 Hz / for AC

• final rated value

• initial rated value

V 48

24

Installation/mounting/dimensions:			
mounting position		any	
Type of mounting		clip-on	
Width	mm	28	
Height	mm	46	
Depth	mm	9	

Certificates/approvals:

Verification of suitability CE / UL / CSA / CCC

General Product Approval

Declaration of Conformity

Test Certificates









Special Test Certificate

Shipping Approval













Shipping Approval

other





Confirmation



Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/industrial-controls/mall

CAx-Online-Generator


http://www.siemens.com/cax


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/3RT2916-1BB00/all

 $Image\ database\ (product\ images,\ 2D\ dimension\ drawings,\ 3D\ models,\ device\ circuit\ diagrams,\ ...)$

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RT2916-1BB00





last change: Jan 21, 2013