



CONTACTOR ASSEMBLY FOR STAR-DELTA STARTERS
 SIZE 14,
 AC-3,
 630KW/400V WITHOUT MAIN CURRENT PATH
 CONNECTION BETWEEN LINE AND DELTA CONTACTOR
 AC OPERATION 110...132V AC,
 50HZ 115...132V AC, 60HZ

General details:

Product function		wye-delta-contactor
Size of the contactor		14
Reference code / according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		K
Reference code / according to DIN EN 61346-2		Q
Width	mm	665
Height	mm	325
Depth	mm	278

Control circuit:

Main circuit:

Operating current / at AC-3 / at 400 V / rated value	A	1,090
Service power / at AC-3 / at 400 V / rated value	kW	630

Connection type:

Design of the electrical connection / for main current circuit		screw-type terminals
---	--	----------------------

Ambient conditions:

Ambient temperature		
• during operating	°C	55 ... -25

Certificates/approvals:

**General Product
Approval**

other



[Declaration of
Conformity](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3TE6804-5CF0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TE6804-5CF0

last change:

Jun 16, 2014