



CONTACTOR RELAY 22E EN 50 011 2NO+2NC,  
TAB CONNECTOR AC OPERATION AC 230/220V 50HZ,  
276/264V 60HZ

### General details:

<b>Size of the contactor</b>		0
<b>Ambient temperature</b>		
• during operating	°C	-25 ... +55
<b>Protection class IP / on the front</b>		IP00
<b>Reference code</b>		
• according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		K
• according to DIN EN 61346-2		K
• according to DIN EN 81346-2		K

### Control circuit:

<b>Voltage type / of control feed voltage</b>		AC
<b>Control supply voltage frequency</b>		
• 1	Hz	50
• 2	Hz	60
<b>Control supply voltage</b>		
• at 50 Hz / at AC / rated value	V	230
• at 60 Hz / at AC / rated value	V	277

### Auxiliary circuit:

<b>Operating current / at AC-15</b>		
• at 230 V / rated value	A	4
• at 400 V / rated value	A	3
<b>Identification number and letter for switching elements</b>		22 E
<b>Number of NC contacts / for auxiliary contacts</b>		2
• lagging switching		0
• delayed switching		0
• asynchronous switching		0
<b>Number of NO contacts / for auxiliary contacts</b>		2
• leading switching		0
• delayed switching		0
• asynchronous switching		0
<b>Number of changeover contacts / for auxiliary contacts</b>		0

#### Connection type:

**Design of the electrical connection / for auxiliary and control current circuit**

tab terminals 2x 2.8 mm

#### Mechanical design:

**Mounting type**

screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022

**Width**

mm 45

**Height**

mm 48

**Depth**

mm 64.5

#### Certificates/approvals:

**General Product Approval**

**Functional Safety / Safety of Machinery**

**Declaration of Conformity**



CCC



CSA



UL

[Type Examination](#)



EG-Konf.

#### Test Certificates

[other](#)

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

#### Shipping Approval

**other**



DNV



GL



LRS



RMRS

[Declaration of Conformity](#)

[Environmental Confirmations](#)

#### Safety:

**Protection against electrical shock**

finger-safe

<b>B10 value / with high demand rate</b> <ul style="list-style-type: none"> <li>• according to SN 31920</li> <li>• note</li> </ul>		400,000 With 0.3 x Ie
<b>T1 value / for proof test interval or service life / according to IEC 61508</b>	a	20

**Further information:**

**Information- and Downloadcenter (Catalogs, Brochures,...)**  
<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**  
<http://www.siemens.com/industrial-controls/mall>

**Cax online generator**  
<http://www.siemens.com/cax>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**  
<http://support.automation.siemens.com/WW/view/en/3TH2022-1AP0/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**  
[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3TH2022-1AP0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TH2022-1AP0)

**last change:** Jun 16, 2014