

MINIATURE POWER RELAY TAB CONNECTOR,
2NO+2NC SNAP-ON MOUNTING ON STANDARD
MOUNTING RAIL DC SOLENOID SYSTEM DC 220V



General details:

Size of the contactor		00
Protection class IP / on the front		IP00
Ambient temperature / during operating	°C	-25 ... +55
Reference code / according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		K
Reference code / according to DIN EN 61346-2		Q
Number of poles / for main current circuit		4
Operating current / at AC-1 / at 400 V • at 40 °C ambient temperature / rated value	A	16

Main circuit:

Number of NC contacts / for main contacts		2
Number of NO contacts / for main contacts		2
Operating current / at AC-3 / at 400 V / rated value	A	9
Operating performance • at AC-3 / at 400 V / rated value • at AC-1 / at 400 V / rated value	kW	4
	kW	10

Control circuit:

Design of activation / of the operating mechanism		conventional
---	--	--------------

Voltage type / of control feed voltage		DC
Number of NC contacts / for auxiliary contacts		
• lagging switching		0
• instantaneous switching		0
Number of NO contacts / for auxiliary contacts		
• leading switching		0
• instantaneous switching		0

Auxiliary circuit:

Design of the electrical connection / for main current circuit		tab terminals 6,3 mm
Design of the electrical connection / for auxiliary and control current circuit		tab terminals 6.3 mm

Mechanical design:

Mounting type		screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
Mounting type / series installation		Yes
Width	mm	45
Height	mm	48
Depth	mm	64.5

Certificates/approvals:

General Product Approval



CCC



CSA



UL

Test Certificates

[Special Test Certificate](#)

Shipping Approval



DNV



PRS



RMRS

other

[Declaration of Conformity](#)

[Environmental Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator:

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WWW/view/en/3TK2022-3BM4/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TK2022-3BM4

last change:

Aug 4, 2014