

SIRIUS CONNECTING CABLE FOR LINKING THE SAFE SPEED MONITOR 3TK2810-1 WITH THE ADAPTER FOR CONNECTION OF ENCODERS (3TK2810-1A / 3TK2810-1B)



**General technical details:**

**Installation environment relating to EMC**

This product is suitable for Class A environments only. It can cause undesired radio-frequency interference in residential environments. If this is the case, the user must take appropriate measures.

**General technical details:**

**Design of the input**

- feedback input
- start input

No

No

**Design of the electrical connection / jumper socket**

No

**Product Function:**

**Acceptability for application**

- position switch monitoring
- EMERGENCY-OFF circuit monitoring
- valve monitoring
- tactile sensor monitoring
- magnetically operated switches monitoring
- safety-related circuits

No

No

No

No

No

No

## Certificates/approvals:

### Verification of suitability

- TÜV (German technical inspectorate) certificate
- UL-registration
- BG BIA certificate

No

No

No

### General Product Approval



## Further information:

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

### Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

### Cax online generator:

<http://www.siemens.com/cax>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WWW/view/en/3TK2810-0A/all>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3TK2810-0A](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TK2810-0A)

last change:

Jul 28, 2014