

PZE X4.1P 24VDC 4n/o

777587



Contact expansion, inputs: 1/2-channel wiring without detection of shorts across contacts, outputs: 4 N/C, UB 24 V DC, width:22.5 mm plug-in screw terminals, contact block for contact expansion in connection with safety-related control components.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;CCC
Application options:	Light beam device mon. Type 2 with t/p;Light beam device mon. Type 2 w/o t/p;Light beam device mon. Type 4;Instantaneous contact expansion
Operating modes:	Single-channel;Dual-channel;without detection of shorts across contacts
Standards:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	24,0
Supply voltage type:	DC
Terminal style:	Plug-in
Terminal type:	Screw terminal
Number of instantaneous safety contacts:	4
Number of delayed safety contacts:	0
Max. current at DC13 I (6 cycles/min):	4.0 A
Voltage at AC15:	230 V
Width dimension:	22.5 mm
Height dimension:	94.0 mm
Depth dimension:	121.0 mm
Gross weight:	195 g
Net weight:	185 g
Ambient temperature:	-10 - 55 °C

Optional accessories



374280

PNOZ X Set plug in screw terminals P1+P2
