

PSEN sg2c-3LPE switch

570801



Safety switch, 1 pushbutton illuminated, 1 pushbutton not illuminated, 1 E-STOP pushbutton.

Technical details

| | |
|-----------------------------|-------------------------|
| Certifications: | CE;cULus Listed;TÜV;FCC |
| Sensor principle: | Transponder |
| Type of coding: | Coded |
| Holding force: | 2000 N |
| Number of OSSD outputs: | 2 |
| Number of inputs: | 2 |
| Connection type: | Federzugklemme steckbar |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Power consumption DC: | 2.0 W |
| Number of pushbutton: | 2 |
| Protection type, housing: | IP54 |
| Number of emergency stops: | 1 |
| Number of control elements: | 2 |
| Width dimension: | 46.5 mm |
| Height dimension: | 465.0 mm |
| Depth dimension: | 74.5 mm |
| Gross weight: | 1170 g |
| Net weight: | 1080 g |
| Ambient temperature: | -20 - 55 °C |

Accessories



570870

PSEN sg escape release pin



570871

PSEN sg auxiliary release pin



570875

PSEN sg color covers (pushbutton)



570890


PSEN sg2 actuator

Optional accessories



570773

PSEN sg2 cover 2pieces



570777

PSEN sg2c Set spring loaded terminals



570890

PSEN sg2 actuator



570870

PSEN sg escape release pin



570871

PSEN sg auxiliary release pin

570875

PSEN sg color covers (pushbutton)

