

PNOZ XV2P 30/24VDC 2n/o 2n/o t

777500



Safety relay (standalone), inputs: 1/2-channel wiring with/without detection of shorts across contacts, outputs: 2 N/O, 2 N/C, automatic/monitored start, UB 24 V DC, width: 45 mm, plug-in screw terminals, monitoring of E-STOP, safety gates, release time 12 levels 0.1 - 30 s.

Technical details

| | |
|--|--|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;CCC |
| Application options: | Instantaneous E-STOP monitoring;Limit switch;Safety gate monitor;Delayed E-STOP monitoring |
| Operating modes: | Single-channel;Automatic reset;Dual-channel;Detection of shorts across contacts;Monitored manual reset |
| Product standard: | EN 60947-5-1 |
| Standards: | EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1 |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Terminal style: | Plug-in |
| Terminal type: | Screw terminal |
| Number of instantaneous safety contacts: | 2 |
| Number of delayed safety contacts: | 2 |
| Safety contact delay type: | Delay-on de-energisation |
| Number of semiconductor outputs: | 0 |
| Selectable times: | 0,10 s;0,50 s;1,00 s;10,00 s;15,00 s;2,00 s;20,00 s;25,00 s;30,00 s;4,00 s;6,00 s;8,00 s |
| Stop category: | 0/1 |
| Max. current at DC13 I (6 cycles/min): | 7.0 A |
| Max. current at AC15: | 5.0 A |
| Width dimension: | 45.0 mm |
| Height dimension: | 94.0 mm |

| | |
|----------------------|-------------|
| Depth dimension: | 121.0 mm |
| Gross weight: | 370 g |
| Net weight: | 360 g |
| Ambient temperature: | -10 - 55 °C |

Optional accessories



374281

PNOZ X Set plug in screw terminals P3+P4