

PSEN ma1.3p-20/PSEN ma1.3-08/8mm/1unit

506226

Magnetic safety switch 3 n/o, M8 male connector, round M12 design, IP67, operating distance 8 mm, PU = 1 piece with M12 actuator coded.



## Technical details

Housing material:	PBT
Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;ECOLAB
Sensor principle:	magnetic
Number of N/O:	3
Connection type:	M8, 8pol. male
Switching voltage:	24 V
Type of switching voltage:	DC
Assured switching distance:	8.0 mm
Assured release distance:	15.0 mm
Protection type, housing:	IP65
Status indicator:	With LED
Design:	Round
Width dimension:	12.0 mm
Height dimension:	11.0 mm
Depth dimension:	59.1 mm
Gross weight:	44 g
Net weight:	30 g
Ambient temperature:	-25 - 70 °C
Operating modes:	Single connection

## Accessories



533150

PSEN cable M8-8sf, 2m



533151

PSEN cable M8-8sf, 5m



533152

PSEN cable M8-8sf, 10m



533153

PSEN cable M8-8sf, 20m



533154

PSEN cable M8-8sf, 30m

## Optional accessories



533150

PSEN cable M8-8sf, 2m



533151

PSEN cable M8-8sf, 5m



533152

PSEN cable M8-8sf, 10m



533153

PSEN cable M8-8sf, 20m

---



533154

PSEN cable M8-8sf, 30m

---



533155

PSEN cable M8-8sf M8-sm, 0.5m

---



533156

PSEN cable M8-8sf M8-8sm, 1m

---



533157

PSEN cable M8-8sf M8-8sm, 2m

---



535120

PSEN ix1 Interface for 4 PSEN 1

---



540329

PSEN converter M8-8sf -- M12-8sm

---