

## PSEnvip RL D M Set

583002



Complete set PSEnvip, consisting of : PSEnvip RL D M, PSEnvip T, PSEnvip AP, PSEnvip AT mag, PSEnvip TP, PSEnvip TN. With bending angle measurement PL e, SIL 3. Approved in accordance with IEC 61496-1 and EN 12622.

### Technical details

|                                 |   |
|---------------------------------|---|
| Certifications:                 | CE;cULus Listed;TÜV                         |
| Operating range (m):            | 0,1 - 10,0                                  |
| Resolution, protection type:    | Reference marker                            |
| Number of OSSD outputs:         | 2   |
| Number of inputs:               | 7   |
| Blanking of safety zones:       | Fixed Blanking                              |
| Application in accordance with: | EN 61496-1;EN 61496-2;IEC 61508;ISO 13849-1 |
| Supply voltage (V):             | 24,0  |
| Supply voltage type:            | DC  |
| Protection type, housing:       | IP54  |
| Width dimension:                | 380.0 mm                                    |
| Height dimension:               | 420.0 mm                                    |
| Depth dimension:                | 230.0 mm                                    |
| Gross weight:                   | 7000 g                                      |
| Net weight:                     | 7000 g                                      |
| Ambient temperature:            | 0 - 50 °C                                   |