

PNOZ mml2p

772021



Configurable safe compact controllers PNOZmulti Mini, connection module for safe connection of decentralised I/O modules.

Technical details

Certifications:	CE;cULus Listed;BG;EAC (Eurasian);TÜV;CCC
Max. cable length shielded:	100 m
Max. cable length unshielded:	30 m
Supply voltage (V):	24,0
Supply voltage type:	DC
Power consumption DC:	101.0 W
Terminal type:	Spring-loaded terminal;Screw terminal
Version for extreme environ. conditions:	Standard
Width dimension:	22.5 mm
Height dimension:	100.0 mm
Depth dimension:	120.0 mm
Gross weight:	115 g
Net weight:	98 g
Ambient temperature:	0 - 60 °C

Accessories



783540

Spring terminals PNOZ mml2p



793540

Screw terminals PNOZ mml2p

Optional accessories

311074

PSS SB BUSCABLE LC



380200

PSS67 Cable M8sf M12sm, 3m



380201

PSS67 Cable M8sf M12sm, 5m

380202

PSS67 Cable M8sf M12sm, 10m



380203

PSS67 Cable M8sf M12sm, 30m



380204

PSS67 Cable M8af M12sm, 3m



380205

PSS67 Cable M8af M12sm, 5m



380206

PSS67 Cable M8af M12sm, 10m



380207

PSS67 Cable M8af M12sm, 30m



380208

PSS67 Cable M12sf M12sm, 3m



380209

PSS67 Cable M12sf M12sm, 5m



380210

PSS67 Cable M12sf M12sm, 10m



380211

PSS67 Cable M12sf M12sm, 30m



380212

PSS67 Cable M12af M12am, 3m



380213

PSS67 Cable M12af M12am, 5m



380320

PSS67 I/O Cable



750020

PNOZ s connector (10 pieces)



783541

Spring terminals PNOZ mml2p 10 pcs.



793541

Screw terminals PNOZ mml2p 10 pcs.