

PSEN op4H-s-30-045/1

630762



Safety light curtain, Type 4, PL e, hand protection (resolution 30 mm), protected field height 450 mm, supply voltage 24 V, terminator M12, transmitter: 4-pin, receiver: 8-pin, connection cable not supplied with the device.

## Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV
Resolution of safety device:	30 mm
Number of beams:	24
Resolution, protection type:	Bulb
Height of protected field:	450 mm
Operating range (m):	0,2 - 19,0
Reaction time:	13.00 ms
Number of OSSD outputs:	2
Blanking:	Laser pointer
Muting:	Fan
Supply voltage (V):	24,0
Supply voltage type:	DC
Protection type, housing:	IP65
Application in accordance with:	CLC/TS 61496-2;EN 61496-1
Width dimension:	32.3 mm
Height dimension:	533.2 mm
Depth dimension:	36.9 mm
Gross weight:	3100 g
Net weight:	2600 g
Ambient temperature:	0 - 55 °C

## Accessories



630303

PSEN op cable axial M12 4-p. shield. 3m



630304

PSEN op cable axial M12 4-p. shield. 5m



630305

PSEN op cable axial M12 4-p. shield. 10m



630306

PSEN op cable angle M12 4-p. shield. 3m



630307

PSEN op cable angle M12 4-p. shield. 5m



630308

PSEN op cable angle M12 4-p. shield. 10m



630309

PSEN op cable axial M12 4-p. shield. 30m



630313

PSEN op cable axial M12 8-p. shield. 3m



630314

PSEN op cable axial M12 8-p. shield. 5m



630315

PSEN op cable axial M12 8-p. shield. 10m

---



630316

PSEN op cable angle M12 8-p. shield. 3m

---



630317

PSEN op cable angle M12 8-p. shield. 5m

---



630318

PSEN op cable angle M12 8-p. shield. 10m

---



630319

PSEN op cable angle M12 4-p. shield. 30m

---



630328

PSEN op cable axial M12 8-p. shield. 30m

---



630329

PSEN op cable angle M12 8-p. shield. 30m

---