

PNOZ s50 C

751500



PNOZsigma Safety relay (standalone). Control/monitoring of inductive actuators, such as brakes and valves, UB 24/48 V DC, max. 3.5/1.75 A continuous current, max. 6.5/3.25 A output current in accordance with PLe and SIL 3, display operation push & turn, plug-in spring-loaded terminals.

Dane

Certyfikacja:	CE;cULus Listed;EAC (Eurasian);TÜV
Możliwości zastosowania:	Sicheres PWM-Schaltgerät
Tryby pracy:	dwukanał.
Normy:	EN 60204-1;EN 62061;EN ISO 13849-1
Typ zacisku:	Zacisk sprężynowy
Napięcie zasilania (V):	24,0
Rodzaj napięcia zasilania 2:	DC
Szerokość:	45.0 mm
Wysokość:	100.0 mm
Głębokość:	120.0 mm
Ciężar brutto:	276 g
Ciężar netto:	257 g
Temperatura pracy:	0 - 55 °C

Akcesoria opcjonalne



751008

PNOZ s Set1spring loaded terminals 45mm



779200

PNOZmulti Chipcard Set 10 piece



779201

PNOZmulti Chipcard 1 piece



779211

Chipcard 1 piece 32kB



779212

PNOZmulti Chipcard Set 10 pieces 32kB



779230

PNOZ Chip Card Reader



779240

PNOZmulti Chipcard Holder (Sparepart)



779250

PNOZmulti Seal 12 pieces



750030

PNOZsigma Chip Card-manager set



750031

SmartCardCommander with SIM-card-adapter