

PNOZ s50 C

751500



PNOZsigma Safety relay (standalone). Control/monitoring of inductive actuators, such as brakes and valves, UB 24/48 V DC, max. 3.5/1.75 A continuous current, max. 6.5/3.25 A output current in accordance with PLe and SIL 3, display operation push & turn, plug-in spring-loaded terminals.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV
Application options:	Sicheres PWM-Schaltgerät
Operating modes:	Dual-channel
Standards:	EN 60204-1;EN 62061;EN ISO 13849-1
Terminal type:	Spring-loaded terminal
Supply voltage (V):	24,0
Supply voltage type 2:	DC
Width dimension:	45.0 mm
Height dimension:	100.0 mm
Depth dimension:	120.0 mm
Gross weight:	276 g
Net weight:	257 g
Ambient temperature:	0 - 55 °C

Optional accessories



751008

PNOZ s Set1spring loaded terminals 45mm



779200

PNOZmulti Chipcard Set 10 piece 8KB



779201

PNOZmulti Chipcard 1 piece 8kb



779211

Chipcard 1 piece 32kB



779212

PNOZmulti Chipcard Set 10 pieces 32kB



779230

PNOZ Chip Card Reader



779240

PNOZmulti Chipcard Holder (Sparepart)



779250

PNOZmulti Seal 12 pieces



750030

PNOZsigma Chip Card-manager set



750031

SmartCardCommander with SIM-card-adapter