

PNOZ e2.1p C 24VDC 2so

784136



Safety relay (standalone) Inputs: Requirement class IIIC in accordance with EN 574 Outputs: 3 N/O, 1 N/C, 2 semiconductor. Automatic start UB 24 V DC, width: 22.5 mm, plug-in spring-loaded terminals Electronic two-hand safety relay.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV
Application options:	Two-hand monitoring Type III C
Operating modes:	Automatic reset;Dual-channel;Detection of shorts across contacts;Self test;with AND input;With OR input
Product standard:	EN 60947-5-1
Standards:	EN 574 TYP III C;EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	24,0
Supply voltage type:	DC
Terminal type:	Spring-loaded terminal
Terminal style:	Plug-in
Number of instantaneous safety outputs:	2 ST
Number of test pulse outputs:	2
Stop category:	0
Width dimension:	22.5 mm
Height dimension:	101.0 mm
Depth dimension:	121.0 mm
Gross weight:	145 g
Net weight:	125 g
Ambient temperature:	-10 - 55 °C

Optional accessories



374290

PNOZ X Set spring loaded terminals P1+P2



774195

Terminal block filter 1



774196

Terminal block filter 2