

PSEnvip R

584100



PSEnvip receiver.

Technical details

| | |
|---------------------------------|--|
| Certifications: | CE;TÜV |
| Operating range (m): | 0,1 - 13,0 |
| Resolution, protection type: | Reference marker |
| Blanking of safety zones: | Fixed Blanking |
| Application in accordance with: | CLC/TS 61496-2;EN 61496-1;EN ISO 13849-1;IEC 61508 |
| Supply voltage (V): | 5,0 |
| Supply voltage type: | DC |
| Protection type, housing: | IP54 |
| Width dimension: | 95.0 mm |
| Height dimension: | 90.0 mm |
| Depth dimension: | 192.0 mm |
| Gross weight: | 2680 g |
| Net weight: | 2410 g |
| Ambient temperature: | 0 - 50 °C |

Accessories



312421

PSSu K F FAU P



312420

PSSu K F FAU B



584569

PSEN cable M12-4sm MIOsm MOVE, 8m



584570

PSEN cable M12-4sm MIOsm MOVE, 10m



584572

PSEN cable M12-4sm MIOsm MOVE, 20m



584571


PSEN cable M12-4sm MIOsm MOVE, 15m

Optional accessories




583200

PSEnvip TP



583203

PSEnvip AT mag



583204

PSEnvip AT mech



583205

PSEnvip MB




583206

PSEnvip MS



583211

PSEnvip AP2



583210

PSEnvip AS2