

PNOZ s6.1 C 48-240VACDC 3 n/o 1 n/c

751156



PNOZsigma Safety relay (standalone). Inputs: 1 N/O, 1 N/C per pushbutton
Outputs: 3 N/O, 1 N/C, 1 semiconductor, UB 48 - 240 V AC/DC, width: 22.5 mm, plug-in spring-loaded terminals. Two-hand control device, monitoring the simultaneity of a two-hand pushbutton.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;KOSHA;CCC
Application options:	Simultaneity monitoring;Two-hand monitoring Type III A
Max. current at DC1:	6.0 A
Voltage at AC1:	240 V
Terminal type:	Spring-loaded terminal
Terminal style:	Plug-in
Stop category:	0
Standards:	EN 574 TYP III A;EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Operating modes:	Dual-channel;Detection of shorts across contacts
Supply voltage (V):	48,0 - 240,0
Width dimension:	22.5 mm
Height dimension:	100.0 mm
Depth dimension:	120.0 mm
Gross weight:	215 g
Net weight:	205 g
Ambient temperature:	-10 - 55 °C

Optional accessories



751004

PNOZ s Setspring loaded terminals 22,5mm



750010

PNOZ s terminator plug (10 pieces)