

PSEN op4H-SL-24-090/1

631125












Safety light guard, Type 4, PL e, hand protection (resolution 24 mm), protected field height 900 mm. Features: Cascading without dead zone, slimline design. Supply voltage 24 V, connector M12, transmitter: 5-pin, receiver 5-pin. Connection cable is not supplied with the device.

Technical details

| | |
|---------------------------------|------------------------|
| Certifications: | CE;cULus Listed;TÜV |
| Product version: | 1.0 |
| Height of protected field: | 900 mm |
| Number of beams: | 48 |
| Operating range (m): | 0,2 - 6,0 |
| Reaction time: | 11.00 ms |
| Number of OSSD outputs: | 2 |
| Muting: | Fan |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Protection type, housing: | IP65 |
| Application in accordance with: | EN 61496-1;IEC 61496-2 |
| Resolution of safety device: | 24 mm |
| Width dimension: | 15.4 mm |
| Height dimension: | 900.0 mm |
| Depth dimension: | 32.6 mm |
| Gross weight: | 2050 g |
| Net weight: | 1100 g |
| Ambient temperature: | 0 - 55 °C |

Optional accessories

| | | |
|-------------------------------------------------------------------------------------|--------|------------------------------------|
|  | 630310 | PSEN op cable axial M12 5-pole 3m |
|  | 630311 | PSEN op cable axial M12 5-pole 5m |
|  | 630312 | PSEN op cable axial M12 5-pole 10m |
|  | 630904 | PSEN op Mirror-165/1 |
|  | 630903 | PSEN op Mirror-120/1 |
|  | 630298 | PSEN cable M12-5sf 20m |
|  | 631183 | PSEN op SL cascading 0,1m |
|  | 631180 | PSEN op SL Bracket C |
|  | 631181 | PSEN op SL Bracket L |



631182

PSEN op SL Bracket O



631184

PSEN op SL cascading 0,5m



631185

PSEN op SL cascading 1m



631186

PSEN op SL Testpiece F 24 mm
