

PSEN sg2c-5LPLLS switch

570817



Safety gate system, safe interlock and safe guard locking device For applications up to SIL CL 3 and PL e. Consisting of 5 pushbuttons: 1. Illuminated pushbutton for activating the safety gate; 2. Push button for accessing & interlocking the safety gate; 3. Illuminated pushbutton; 4. Illuminated pushbutton; 5. Section stop pushbutton Delivery scope: Sensing device with pushbuttons (spare part).

Dane

Certyfikacja:	CE;cULus Listed;TÜV;FCC
Zasada działania czujnika:	Transponder
Rodzaj kodowania:	Kodowany
Siła mocująca, kierunek kątowy:	2000 N
Liczba wyjść OSSD:	2
Liczba wejść:	2
Rodzaj przyłącza:	Federzugklemme steckbar
Napięcie zasilania (V):	24,0
Rodzaj napięcia zasilania:	DC
Pobór mocy DC:	2.0 W
Numer przycisku:	2
Stopień ochrony obudowy:	IP54
Liczba elementów sterujących:	4
Liczba wyłączników operacyjnych:	1
Szerokość:	46.5 mm
Wysokość:	555.0 mm
Głębokość:	74.5 mm
Ciężar brutto:	1270 g
Ciężar netto:	1180 g
Temperatura pracy:	-20 - 55 °C

Akcesoria



570870

PSEN sg escape release pin



570871

PSEN sg auxiliary release pin



570875

PSEN sg color covers (pushbutton)



570890

PSEN sg2 actuator

Akcesoria opcjonalne



570773

PSEN sg2 cover 2pieces



570777

PSEN sg2c Set spring loaded terminals



570890

PSEN sg2 actuator



570870

PSEN sg escape release pin



570871

PSEN sg auxiliary release pin

570875

PSEN sg color covers (pushbutton)

