

PSEN cs4.1 M12/8-1.5m/PSEN cs4.1 1unit

541114



RFID safety switch, 2 safe SC outputs, male connector M12/8- pin on 1.5 m cable, for applications up to SIL 3 or PL e or Cat. 4, IP67, typ. operating distance 11 mm, Sao = 8 mm, Sar = 20 mm, PU = 1piece fully coded switch with actuator, max. 8 teach-in processes.

Technical details

| | |
|-----------------------------|---|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;FCC;IC |
| Sensor principle: | Transponder |
| Type of coding: | Fully coded |
| Number of OSSD outputs: | 2 |
| Number of inputs: | 2 |
| Connection type: | M12, 8pol. male |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Power consumption DC: | 1.0 W |
| Assured switching distance: | 8.0 mm |
| Assured release distance: | 20.0 mm |
| Protection type, housing: | IP6K9K |
| Width dimension: | 26.0 mm |
| Height dimension: | 37.0 mm |
| Depth dimension: | 18.0 mm |
| Gross weight: | 140 g |
| Net weight: | 110 g |
| Ambient temperature: | -25 - 70 °C |

Accessories



533150

PSEN cable M8-8sf, 2m



533151

PSEN cable M8-8sf, 5m



533152

PSEN cable M8-8sf, 10m



533153

PSEN cable M8-8sf, 20m



533154

PSEN cable M8-8sf, 30m

Optional accessories



533150

PSEN cable M8-8sf, 2m



533151

PSEN cable M8-8sf, 5m



533152

PSEN cable M8-8sf, 10m



533153

PSEN cable M8-8sf, 20m



533154

PSEN cable M8-8sf, 30m



533155

PSEN cable M8-8sf M8-sm, 0.5m



533156

PSEN cable M8-8sf M8-8sm, 1m



533157

PSEN cable M8-8sf M8-8sm, 2m



540329

PSEN converter M8-8sf -- M12-8sm



773603

PDP67 F 4 code



540340

PSEN cable M12-8sf M12-8sm, 2m



540341

PSEN cable M12-8sf M12-8sm, 5m



540343

PSEN cable M12-8sf M12-8sm, 20m



540344

PSEN cable M12-8sf M12-8sm, 30m



540342

PSEN cable M12-8sf M12-8sm, 10m



540130

SDD ES ETH



540132

SDD ES PROFIBUS



540337

PSEN Y junction M8-M12/M12 PIGTAIL
