

PSEN sg2c-3LPC unit

570808



Safety gate system includes safe interlocking device with guard locking. According to DIN EN60947-5-3. For applications up to SIL CL3 or Ple. Device type: 1. illuminated push button 2. push button 3. blind cover Scope of delivery: Sensor unit with push buttons including color covers and escape release pin as well as actuator (bolt) for doors with hinges left or right."

Dane

| | |
|---------------------------------|-------------------------|
| Certyfikacja: | CE;cULus Listed;TÜV;FCC |
| Zasada działania czujnika: | Transponder |
| Rodzaj kodowania: | Kodowany |
| Siła mocująca, kierunek kątowy: | 2000 N |
| Liczba wyjść OSSD: | 2 |
| Liczba wejść: | 2 |
| Rodzaj przyłącza: | Federzugklemme steckbar |
| Napięcie zasilania (V): | 24,0 |
| Rodzaj napięcia zasilania: | DC |
| Pobór mocy DC: | 2.0 W |
| Numer przycisku: | 2 |
| Stopień ochrony obudowy: | IP54 |
| Liczba elementów sterujących: | 2 |
| Szerokość: | 200.0 mm |
| Wysokość: | 465.0 mm |
| Głębokość: | 108.0 mm |
| Ciężar brutto: | 2950 g |
| Ciężar netto: | 2570 g |
| Temperatura pracy: | -20 - 55 °C |

Aksesoria opcjonalne



570773

PSEN sg2 cover 2pieces



570777

PSEN sg2c Set spring loaded terminals



570890

PSEN sg2 actuator



570870

PSEN sg escape release pin



570871

PSEN sg auxiliary release pin



570875

PSEN sg color covers (pushbutton)