

PSEN sg2c-5LPKLC-M12/5 unit

570832



Safety gate system, safe interlock and safe guard locking device For applications up to SIL CL 3 and PL e. Consisting of 5 pushbuttons: 1. Illuminated pushbutton for activating the safety gate; 2. Push switch for accessing & interlocking the safety gate; 3. Key switch (3 positions) 4. Illuminated pushbutton; 5. Blind cover M12/5 connection with enable switch
Delivery scope: Sensing device with pushbuttons incl. colour caps and Escape release bar and actuator for right or left hinged gates.

Dane


| | |
|---------------------------------|-------------------------|
| Certyfikacja: | CE;cULus Listed;TÜV;FCC |
| Zasada działania czujnika: | Transponder |
| Rodzaj kodowania: | Kodowany |
| Siła mocująca, kierunek kątowy: | 2000 N |
| Liczba wyjść OSSD: | 2 |
| Liczba wejść: | 2 |
| Rodzaj przyłącza: | Federzugklemme steckbar |
| Napięcie zasilania (V): | 24,0 |
| Rodzaj napięcia zasilania: | DC |
| Pobór mocy DC: | 2.0 W |
| Numer przycisku: | 2 |
| Stopień ochrony obudowy: | IP54 |
| Liczba elementów sterujących: | 4 |
| Szerokość: | 200.0 mm |
| Wysokość: | 568.0 mm |
| Głębokość: | 108.0 mm |
| Ciężar brutto: | 3060 g |
| Ciężar netto: | 2690 g |
| Temperatura pracy: | -20 - 55 °C |

Akcesoria opcjonalne



401110

PIT en1.0p-5m-s



570773

PSEN sg2 cover 2pieces



570777

PSEN sg2c Set spring loaded terminals



570890

PSEN sg2 actuator



570870

PSEN sg escape release pin



570871

PSEN sg auxiliary release pin



570875

PSEN sg color covers (pushbutton)